


REVISIONS																		
LTR	DESCRIPTION								DATE				APPROVED					
A	Update references, technical data, contact information, distribution statement.								24 April 2008				Abdonasser Abdouni					
B	Updated Vendor PINS.								30 July 2009				Abdonasser Abdouni					
Prepared in accordance with ASME Y14.100 Source control drawing																		
REV																		
PAGE																		
REV STATUS OF PAGES	REV		B	A	A	B												
	PAGE		1	2	3	4												
PMIC N/A		PREPARED BY							DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OHIO 43218-3990									
		Ron Gary																
Original date of drawing 20 April 2001		CHECKED BY							TITLE									
		Lee Surowiec							CONNECTOR, PLUG, ELECTRICAL, RF, SERIES BNC, RIGHT ANGLE, FOR LOW SMOKE CABLES									
		APPROVED BY																
		Rob Heber																
		SIZE	CAGE CODE						DWG. NO.				01012					
		A	037Z3															
	REV	B					PAGE		1		OF	4						



NOTES:

1. Dimensions are in inches. Metric equivalents are in parenthesis.
2. Metric equivalents are given for reference purposes only.
3. All undimensioned pictorial configurations are for reference purposes only.
4. Series BNC, pin contact interface, in accordance with MIL-STD-348.

FIGURE 1. General configuration.

DEFENSE SUPPLY CENTER, COLUMBUS COLUMBUS, OH 43218-3990	SIZE A	CAGE CODE 037Z3	DWG NO. 01012
		REV A	PAGE 2

ENGINEERING DATA:

This document covers the requirements for radio frequency connectors accommodating special low smoke coaxial cables.

REQUIREMENTS:

These connectors shall conform to all the requirements of the latest issue of DSCC drawing 84148, figure 1 herein, and MIL-PRF 39012/20, and accommodate the cables listed in table I, with the following additions and exceptions.

Electrical: Shall be in accordance with MIL-PRF-39012/20.

Mechanical: Shall be in accordance with MIL-PRF-39012/20.

Environmental: Shall be in accordance with MIL-PRF-39012/20.

TABLE I. Cable accommodation.

Part or Identifying Number (PIN) <u>1/</u> <u>2/</u>	Applicable cable
01012BBSA @	M17/220-00001
01012BBSB #	M17/221-00001
01012BBSC &	M17/222-00001
01012BBSD \$	M17/223-00001
01012BBSE %	M17/224-00001
01012BBSF	M17/225-00001

1/ These connectors have captivated center contacts.

2/ These connectors are assembled using the MIL-C-22520/5 crimp tool and using the following crimp dies:

@ M22520/5-05
M22520/5-07
& M22520/5-29
\$ M22520/5-25
% M22520/5-27

DEFENSE SUPPLY CENTER, COLUMBUS
COLUMBUS, OH 43218-3990

SIZE
A

CAGE CODE

037Z3

REV

A

DWG NO.

01012

PAGE

3

Approved sources of supply. Approved sources of supply are listed herein. Additional sources will be added as they become available. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to Defense Supply Center Columbus, ATTN: DSCC-VAI, P.O. Box 3990, Columbus, OH 43218-3990 or emailed to RFConnector@dla.mil.

DSCC drawing PIN	Vendor similar PIN <u>1/</u>	Vendor CAGE number
01012BBSA	(3190-849) Superseded by 1007320A001-000	00795
01012BBSB	(3190-1149) Superseded by 1007311A001-000	
01012BBSC	(3190-1175) Superseded by 1007348A001-000	
01012BBSD	(3190-855) Superseded by 1007300A001-000	
01012BBSE	(3190-1197) Superseded by 1007318A001-000	
01012BBSF	(3190-860) Superseded by 1007319A001-000	

1/ Parts must be purchased to this DSCC PIN to assure all performance requirements and test are met.

Vendor CAGE
number

00795

Vendor name
and address

Delta Electronics
416 Cabot Street
Beverly, MA 01915

DEFENSE SUPPLY CENTER, COLUMBUS
COLUMBUS, OH 43218-3990

SIZE
A

CAGE CODE

037Z3

REV **B**

DWG NO.

01012

PAGE **4**