

MILITARY SPECIFICATION

CABLES, RADIO FREQUENCY, SEMIRIGID,

COAXIAL, SEMI-AIR-DIELECTRIC,

GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification MIL-C-22931,
10 February 1968, and is mandatory for use by all Departments and
Agencies of the Department of Defense.

SPECIFICATION SHEETS

- MIL-C-22931/9 - Cables, Radio Frequency, Semirigid, Coaxial,
Semi-Air-Dielectric, .500 and .530 Inch
Outside Diameter, 50 Ohms.
- MIL-C-22931/10 - Cables, Radio Frequency, Semirigid, Coaxial,
Semi-Air-Dielectric, .500 Inch Outside
Diameter, 75 Ohms.
- MIL-C-22931/11 - Cables, Radio Frequency, Semirigid, Coaxial,
Semi-Air-Dielectric, .875 to 1.005 Inches
Outside Diameter, 50 Ohms.
- MIL-C-22931/12 - Cables, Radio Frequency, Semirigid, Coaxial,
Semi-Air-Dielectric, .875 and 1.005 Inches
Outside Diameter, 75 Ohms.
- MIL-C-22931/13 - Cables, Radio Frequency, Semirigid, Coaxial,
Semi-Air-Dielectric, 1.625 to 1.830 Inches
Outside Diameter, 50 Ohms.
- MIL-C-22931/14 - Cables, Radio Frequency, Semirigid, Coaxial,
Semi-Air-Dielectric, 1.625 Inches Outside
Diameter, 75 Ohms.
- MIL-C-22931/15 - Cables, Radio Frequency, Semirigid, Coaxial,
Semi-Air-Dielectric, 2.850 and 3.125 Inches
Outside Diameter, 50 Ohms.
- MIL-C-22931/16 - Cables, Radio Frequency, Semirigid, Coaxial,
Semi-Air-Dielectric, 3.125 inches Outside
Diameter, 75 Ohms.

Preparing activity:
Navy - EC

(Project 6145-0550)

FSC 6145