


DETAIL A



MALE FIXED JACKSCREW

① DETAIL B

Inches	mm	Inches	mm
.001	0.03	.138	3.51
.008	0.20	.156	3.96
.010	0.25	.188	4.78
.015	0.38	.195	4.95
.018	0.46	.200	5.08
.020	0.51	.225	5.72
.022	0.56	.232	5.89
.025	0.64	.250	6.35
.040	1.02	.283	7.19
.043	1.09	.312	7.92
.086	2.18	.375	9.52
.112	2.84	.445	11.30
.135	3.43	.450	11.43
.137	3.48	.482	12.24

FIGURE 1. Connector, pin contacts, class S - Continued.

Dash no. (see notes 4 and 5)	Shell size	No. of contacts	Insert arrangement no section (see note 6)	A *.015 (0.38)	B *.015 (0.38)	C *.005 (0.12)	D *.005 (0.12)	E *.005 (0.12)	F *.005 (0.12)	G BSC	H *.005 (0.12)	J *.025 (0.63)	Weight (max)(with contacts) grams
1	8	14	10 No.1	1.520 (38.60)	.725 (18.41)	.800 (20.32)	.548 (13.91)	.688 (17.47)	.436 (11.07)	1.200 (30.48)	.050 (1.27)	1.360 (34.54)	13.5
2	10	38	20 No.1	1.945 (49.40)	.725 (18.41)	1.220 (30.98)	.548 (13.91)	1.108 (28.14)	.436 (11.07)	1.625 (41.27)	.050 (1.27)	1.360 (34.54)	20.0
3	12	88	30 No.1	2.780 (70.61)	.725 (18.41)	2.060 (52.32)	.548 (13.91)	1.948 (49.47)	.436 (11.07)	2.460 (62.48)	.050 (1.27)	1.360 (34.54)	27.0
4	14	108	40 No.1	1.990 (50.54)	1.077 (27.35)	1.444 (36.67)	.897 (22.78)	1.332 (33.83)	.785 (19.93)	1.718 (43.63)	.058 (1.47)	1.360 (34.54)	33.5
5	16	132	50 No.1	2.790 (70.86)	.902 (22.91)	2.068 (52.52)	.732 (18.59)	1.956 (49.68)	.620 (15.74)	2.470 (62.73)	.100 (2.54)	1.360 (34.54)	38.5
6	18	244	60 No.1	4.128 (104.85)	.902 (22.91)	3.410 (86.61)	.732 (18.59)	3.304 (83.92)	.630 (16.00)	3.808 (96.72)	.100 (2.54)	1.360 (34.54)	47.0
7	8	14	10 No.1	1.520 (38.60)	.725 (18.41)	.800 (20.32)	.548 (13.91)	.688 (17.47)	.436 (11.07)	1.200 (30.48)	.050 (1.27)	.898 (22.80)	13.5
8	10	38	20 No.1	1.945 (49.40)	.725 (18.41)	1.220 (30.98)	.548 (13.91)	1.108 (28.14)	.436 (11.07)	1.625 (41.27)	.050 (1.27)	.898 (22.80)	20.0
9	12	88	30 No.1	2.780 (70.61)	.725 (18.41)	2.060 (52.32)	.548 (13.91)	1.948 (49.47)	.436 (11.07)	2.460 (62.48)	.050 (1.27)	.898 (22.80)	27.0
10	14	108	40 No.1	1.990 (50.54)	1.077 (27.35)	1.444 (36.67)	.897 (22.78)	1.332 (33.83)	.785 (19.94)	1.718 (43.63)	.058 (1.47)	.898 (22.80)	33.5
11	16	132	50 No.1	2.790 (70.86)	.902 (22.91)	2.068 (52.52)	.732 (18.59)	1.956 (49.68)	.620 (15.74)	2.470 (62.73)	.100 (2.54)	.898 (22.80)	38.5
12	18	244	60 No.1	4.128 (104.85)	.902 (22.91)	3.410 (86.61)	.732 (18.59)	3.304 (83.92)	.630 (16.00)	3.808 (96.72)	.100 (2.54)	.898 (22.80)	47.0

NOTES

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Millimeters are in parentheses.
4. Dash number shall include N, V, W, X, Y, or Z to indicate polarization.
5. Dash numbers 1 through 6 are supplied with male turning jackscrews; dash numbers 7 through 12 are supplied with male fixed jackscrews.
6. For insert arrangements, see MIL-STD-1632.

① FIGURE 1. Connector, pin contacts, class S - Continued.

MIL-C-28804/8D

REQUIREMENTS:

Dimensions and configuration: See figure 1.

- ① Mating end of the contacts: Shall be in accordance with MIL-C-28804/9. Solder contacts may be stamp formed from strip material.
- Mating connectors: M28804/8-1 through -6 mate with M28804/1-1 through -6, M28804/3-1 through -6, M28804/5-1 through -6, M28804/7-1 through -6. M28804/8-7 through -12 mate with M28804/1-7 through -12, M28804/3-7 through -12, M28804/5-7 through -12, and M28804/7-7 through -12.
- ① Part or Identifying Number (PIN): M28804/8- (dash number from figure 1 and a suffix letter code to define polarization. See figure 1, note 4 herein, and MIL-C-28804).
- ① Dielectric withstanding voltage shall be in accordance with MIL-C-28804, except that the test voltages shall be as specified in table 1.

① TABLE I. Test voltage (rms 60 Hz ac volts). 1/

Altitude (feet)	Moisture conditioned (see 4.6.12) samples	All other samples
Sea level	600	1200
70,000	---	500

1/ These are not working voltages.

- ① Contact resistance shall be in accordance with MIL-C-28804.

CONCLUDING MATERIAL

Custodians.

Army - CR
Navy - EC
Air Force - 85

Preparing activity.

Navy - EC

Agent:

DLA - ES

Review activities.

Army - AT, M1
Navy - AS
Air Force - 85, 99
DLA - ES

(Project 5935-3763-08)

User activities:

Army - AM, AR, ME
Navy - MC