

INCH-POUND

MIL-DTL-32139/9A
w/AMENDMENT 1
21 March 2022
SUPERSEDING
MIL-DTL-32139/9A
11 February 2020

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, RECTANGULAR, NANOMINIATURE,
DUAL ROW, PLUG, REAR PANEL MOUNT, POLARIZED SHELL, PIG TAIL,
PIN CONTACTS, CRIMP TYPE, INSULATED WIRE, GASKET SEAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-32139.





FIGURE 1. Plug, Rear Panel Mount dimensions and configurations.



Shown with Gasket

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

FSC 5935



MIL-DTL-32139/9A
w/AMENDMENT 1

Size	A BSC	B BSC	C BSC	D	E	F	G	H
9	.270 (6.86)	.160 (4.06)	.566 (14.38)	.175 (4.45)	.688 (17.48)	.808 (20.52)	#0-80 UNF-2B	.280 (7.11)
15	.345 (8.76)	.235 (5.97)	.641 (16.28)	.250 (6.35)	.763 (19.38)	.883 (22.43)	#0-80 UNF-2B	.280 (7.11)
21	.420 (10.67)	.310 (7.87)	.716 (18.19)	.325 (8.26)	.838 (21.29)	.958 (24.33)	#0-80 UNF-2B	.280 (7.11)
25	.470 (11.94)	.360 (9.14)	.766 (19.46)	.375 (9.53)	.888 (22.56)	1.008 (25.60)	#0-80 UNF-2B	.280 (7.11)
31	.545 (13.84)	.435 (11.05)	.841 (21.36)	.450 (11.43)	.963 (24.46)	1.083 (27.51)	#0-80 UNF-2B	.280 (7.11)
37	.620 (15.75)	.510 (12.95)	.916 (23.27)	.525 (13.34)	1.038 (26.37)	1.158 (29.41)	#0-80 UNF-2B	.280 (7.11)
51	.795 (20.19)	.685 (17.40)	1.091 (27.71)	.700 (17.78)	1.213 (30.81)	1.333 (33.86)	#0-80 UNF-2B	.280 (7.11)
65	.970 (24.64)	.860 (21.84)	1.266 (32.16)	.875 (22.23)	1.388 (35.26)	1.508 (38.30)	#0-80 UNF-2B	.280 (7.11)
69	1.020 (25.91)	.910 (23.11)	1.316 (33.43)	.925 (23.50)	1.438 (36.53)	1.558 (39.57)	#0-80 UNF-2B	.280 (7.11)
85	1.246 (31.65)	1.110 (28.19)	1.568 (39.83)	1.125 (28.58)	1.690 (42.93)	1.810 (45.97)	#2-56 UNC-2B	.305 (7.75)

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are $\pm .005$ inch (0.13 mm) angular tolerance $\pm 2^\circ$.
4. Shell shall be flush to insulator within $\pm .004$ inch (0.10 mm).
5. 30 AWG wire is the largest wire size that can be used in the connector assembly

FIGURE 1. Plug, Rear Panel Mount dimensions and configurations - Continued.

MIL-DTL-32139/9A
w/AMENDMENT 1

NOTES:

1. Panel cutout is sized to allow connector mounting with either lobes up or down orientation.
2. Recommended panel thickness .100 MAX.

FIGURE 3. Panel cutout dimensions and configurations - Continued.

REQUIREMENTS:

Dimensions and configuration see figures 1, 2, and 3.

This specification sheet describes the pin side of a rectangular connector. This connector uses reverse gender contacts, i.e., the live pin recessed in the insulator with the static socket protruding from a shrouded interface.


Contact connection: The pin contact, which is recessed in the insulator, is normally connected to the live side of the circuit.

To protect the electrical enclosure equipment, the panel mount connector shall seal from the outside environmental conditions such as dust and splashed water.

Interface dimensions according to MIL-DTL-32139/3.

Mating receptacle: Shall be in accordance with MIL-DTL-32139/4.

Part of Identifying Number (PIN):



MIL-DTL-32139/9A
w/AMENDMENT 1

Wire type ^{1/}

Insert arrangement

A = 9
B = 15
C = 21
D = 25
E = 31
F = 37
G = 51
H = 65
J = 69
K = 85

01 = NEMA HP3-ETXBBB9	6 inches (152 mm) long
02 = NEMA HP3-ETXBBB9	18 inches (457 mm) long
03 = NEMA HP3-ETXBBB9	36 inches (914 mm) long
04 = NEMA HP3-ETXBBB()	6 inches (152 mm) long ^{2/}
05 = NEMA HP3-ETXBBB()	18 inches (457 mm) long ^{2/}
06 = NEMA HP3-ETXBBB()	36 inches (914 mm) long ^{2/}
07 = M22759/33-30-9	6 inches (152 mm) long ^{3/ 4/}
08 = M22759/33-30-9	18 inches (457 mm) long ^{3/ 4/}
09 = M22759/33-30-9	36 inches (914 mm) long ^{3/ 4/}
10 = M22759/33-30-()	6 inches (152 mm) long ^{2/ 3/ 4/}
11 = M22759/33-30-()	18 inches (457 mm) long ^{2/ 3/ 4/}
12 = M22759/33-30-()	36 inches (914 mm) long ^{2/ 3/ 4/}
13 = 04047-30A-9	6 inches (152 mm) long
14 = 04047-30A-9	18 inches (457 mm) long
15 = 04047-30A-9	36 inches (914 mm) long
16 = 04047-30A-()	6 inches (152 mm) long ^{2/}
17 = 04047-30A-()	18 inches (457 mm) long ^{2/}
18 = 04047-30A-()	36 inches (914 mm) long ^{2/}
19 = M22759/47-30-9	6 inches (152 mm) long
20 = M22759/47-30-9	18 inches (457 mm) long
21 = M22759/47-30-9	36 inches (914 mm) long
22 = M22759/47-30-()	6 inches (152 mm) long ^{2/}
23 = M22759/47-30-()	18 inches (457 mm) long ^{2/}
24 = M22759/47-30-()	36 inches (914 mm) long ^{2/}
25 = M22759/51-30-9	6 inches (152 mm) long
26 = M22759/51-30-9	18 inches (457 mm) long
27 = M22759/51-30-9	36 inches (914 mm) long
28 = M22759/51-30-()	6 inches (152 mm) long ^{2/}
29 = M22759/51-30-()	18 inches (457 mm) long ^{2/}
30 = M22759/51-30-()	36 inches (914 mm) long ^{2/}
31 = M22759/52-30-9	6 inches (152 mm) long
32 = M22759/52-30-9	18 inches (457 mm) long
33 = M22759/52-30-9	36 inches (914 mm) long
34 = M22759/52-30-()	6 inches (152 mm) long ^{2/}
35 = M22759/52-30-()	18 inches (457 mm) long ^{2/}
36 = M22759/52-30-()	36 inches (914 mm) long ^{2/}

Hardware

T = Female Thread

Shell and finish

S = Passivated stainless steel shell
T = Titanium

Space class

Blank for non-space applications.

S = Space class

Mounting Thread Option

Omit For #2-56 UNC-2B

M = M2X0.4 6H

MIL-DTL-32139/9A
w/AMENDMENT 1

- 1/ Pig tail wire lead tolerance is +1.00 inch/-0.0 inch (25.4/-0.0 mm).
- 2/ Color coding in accordance with MIL-STD-681, system 1, except using ten solid colors only in repeating sequence.
- 3/ Corrosion has been experienced on M32139 connectors that are pre-wired with M22759/33-30-9 or M22759/33-30-() wires and stored in a sealed environment. CAUTION SHOULD BE EXERCISED WHEN USING THIS WIRE.
- 4/ Wire M22759/33 use insert wire strip tool SAE AS5768/1, T7 or B7 for 30 gauge wire.

Gasket Material

Omit for no gasket

01 = Fluorosilicone IAW MIL-DTL-25988, Type II, Class I, Grade 70

02 = Passivated Silver Plated Aluminum Filled Fluorsilicone IAW MIL-DTL-83528, Type "D" (CHO-Seal 1298 or Equivalent)

03 = Nickel Plated Aluminum Filled Fluorosilicone, (CHO-Seal 6503 or Equivalent)

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-32139, this document references the following:

MIL-DTL-32139/3
MIL-DTL-32139/4
MIL-DTL-25988
MIL-DTL-83528
MIL-STD-681
SAE AS5768/1

CONCLUDING MATERIAL

Custodians:

Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:

DLA - CC

(Project 5935-2022-064)

Review activities:

Army - MI

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil>.