

DETAIL SPECIFICATION

ADAPTER, HYDRAULIC AND PNEUMATIC, 37 DEGREE FLARE TUBE FITTING TO
O-RING FACE SEAL CONNECTORS, 1500 TO 3000 PSI AND -65°F TO 250°F,
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-32460, dated 10 March 2020.

SPECIFICATION SHEETS

- MIL-DTL-32460/1 - Fitting, Adapter, Straight, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Male
- MIL-DTL-32460/2 - Fitting, Adapter, 45 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Male
- MIL-DTL-32460/3 - Fitting, Adapter, 90 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Male
- MIL-DTL-32460/4 - Fitting, Adapter, Straight, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Bulkhead
- MIL-DTL-32460/5 - Fitting, Adapter, 45 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Bulkhead
- MIL-DTL-32460/6 - Fitting, Adapter, 90 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Bulkhead
- MIL-DTL-32460/7 - Fitting, Adapter, Straight, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS, Female Swivel
- MIL-DTL-32460/8 - Fitting, Adapter, 45 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS, Female Swivel
- MIL-DTL-32460/9 - Fitting, Adapter, 90 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS, Female Swivel

CONCLUDING MATERIAL

Custodians:

Army - AT
Navy - AS
Air Force - 71
DLA - CC

Preparing activity:

DLA - CC

Review activities:

Army - AR
Navy - CG, SA, SH

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil>.

