

DETAIL SPECIFICATION SHEET

SWITCHES, TOGGLE, DOUBLE POLE, 4 AMPERES, LOW LEVEL, ENVIRONMENTALLY SEALED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and [MIL-DTL-83731](#).




FIGURE 1. PC Terminals.




FIGURE 2. Solder Lug Terminals.




FIGURE 4. Standard Hardware and Panel Cut-out.







FIGURE 3. Standard and Short Levers Lengths.



1 Locked Position



2 Locked Positions



3 Locked Positions

FIGURE 5. Locking Levers.




FIGURE 6. Terminal Dimensions

REQUIREMENTS:

Temperature characteristic: -40°C to +85°C.

Shock type: (50 g's sine wave) method 213, test condition A, [MIL-STD-202-213](#).

Sinusoidal vibration grade: 1 (10 to 500 Hz).

Operating characteristics:

Enclosure Design: 3 (watertight).

Finish: Shall be corrosion resistant, black and lusterless.

Dielectric withstanding voltage:

Sea level: 1,000 V rms between terminals
2,000 V rms between poles
2,000 V rms between terminals and frame

Electrical endurance:

At 2A, 250VAC or 4A, 28VDC: 10,000 cycles.
At low level (50mV, 10mA): 20,000 cycles

Electrical ratings: (Maximum current/voltage rating with resistive load)

2A/250 VAC, 4A/125 VAC, or 4A/28 VDC

Contact bounce: 2ms max.

Sand and dust: Applicable.

Explosion: Not Applicable.

Low level circuit: Applicable.


Qualification: Inspection table of [MIL-DTL-83731](#)

Inductive Load: Not Applicable.

Lamp Load: Not Applicable.

Seal: Sea level only.

Military Part or Identifying Number (PIN): The PIN shall consist of the prefix M83731/23, followed in order by the appropriate numeric designator for terminal style and plunger length.



Example: M83731/23-24B02V, PC Terminals, Momentary (ON-ON-MOM), No Tip, 2 Locked Position Lever.

TABLE I. Electrical Functions

6	ON	-	ON
9	ON	OFF	ON
7	MOM	OFF	MOM
8	ON	OFF	MOM
4	ON	ON	ON
	ON	ON	MOM
	MOM	ON	MOM
5		ON	MOM

TABLE II. Momentary

A	Non-Momentary		
B <u>1/</u>	ON	ON	MOM
C <u>1/</u>	MOM	ON	MOM
D	Momentary		

1/ Function 4 Only.




FIGURE 7. Terminal Identification






FIGURE 8. Wiring for 3-Way Switches (Function 4).

TABLE III. Lever Positions and Connections

Function	I	II	III (Flat)
6	ON (1-3)-4 (5-7)-8	-	ON (1-3)-2 (5-7)-6
7 8 9	MOM ON ON 1-2 4-5	OFF OFF OFF	MOM MOM ON 1-3 4-6
4	ON ON MOM 1-2 4-5	ON ON ON 1-3 4-5	ON MOM MOM 1-3 4-6
5		ON 1-2 4-5	MOM 1-3 4-6

Referenced Documents:

[MIL-DTL-83731](#)
[MIL-STD-202-213](#)

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
 Army - CR
 Air Force - 85
 Navy - EC
 DLA - CC

Preparing activity:
 DLA - CC

 (Project 5930-2025-045)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil/>.