

MILITARY SPECIFICATION SHEET
 ELECTRON TUBE, NEGATIVE GRID (MICROWAVE)

1/ TYPE DOD-038

This specification is approved for use by the Electronics Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Planar triode
 See figure 1
 Mounting position: Any
 Weight: 0.06 ounce (1.7 grams) nominal

ABSOLUTE RATINGS: Grid-pulsed oscillator service

Parameter:	F	Ef	Eb	Ec	Rk	Ib	ib	Ic	ic	tp	Du	Pp	TE
Unit:	GHz	V	Vdc	Vdc	Ohms	mAdc	a	mAdc	a	μs	---	W	°C
Maximum:	6.0	6.6	550	-50	---	10	1.0	5.0	0.5	1.0	0.01	4.5	250
Minimum:	---	6.0	---	---	---	---	---	---	---	---	---	---	---

(Note 1)

TEST CONDITIONS: --- 6.3 125 --- 82 --- --- --- --- --- --- ---

GENERAL:

Qualification - Required

1/ Replaces GE type Y-1124-3

Ⓑ denotes changes

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFEC- TIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
							MIN	MAX	
1031	<u>Qualification inspection</u>								
---	Sweep-frequency vibration fatigue	6	$E_b = E_c = 0$; $E_f = 6.3 \text{ V}$	---	---	---	---	---	---
---	Sweep-frequency vibration fatigue test end points:								
1031	Low-frequency vibration	-		---	---	E_p	---	15	mVac
1336	Heater-cathode leakage	-		---	---	I_{hk}	---	20	μAdc
1306	Transconductance	-		---	---	S_m	12,000	---	μmhos
1301	Heater current	-		---	---	I_f	198	232	mA
	<u>Quality conformance inspection, part 1</u>								
1301	Heater current	-		0.65	II	I_f	198	232	mA
1336	Heater-cathode leakage	-		0.65	II	I_{hk}	---	20	μAdc
(B) 1306	Transconductance	8	$C_k = 1,000 \mu\text{F}$	---	---	S_m	16,000	24,000	μmhos
1261	Electrode voltage (grid)	-	$R_k = 0$; $E_c/I_b = 0.1 \text{ mAdc}$	0.65	II	E_c	---	-6.0	Vdc
4250	Pulsed oscillation	-	$F = 5.7 \text{ GHz}$; $E_{bb} = 400 \text{ Vdc}$; $e_{gy}/I_b = 0.6 \text{ a}$; $t_p = 1 \mu\text{s}$; $D_u = 0.016$; $p_{rr} = 16,000$; $R_g = 100 \text{ ohms}$; $E_g = -20 \text{ Vdc}$	0.65	II	p_o	20	---	w
(B) ---	Grid pulse voltage	8	$E_b = 400 \text{ Vdc}$; $E_c = -20 \text{ V}$; $t_p = 1 \mu\text{s}$; $p_{rr} = 1,000$; $e_{gy}/I_p = 1.2 \text{ a}$	---	---	e_{gy}	---	50	v
1211	Insulation of electrodes	-		0.65	II	R	50	---	Meg
4303	Cathode warmup time	2	Grid pulse voltage conditions	0.65	II	t	---	0.75	sec

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFEC- TIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
							MIN	Max	
	<u>Quality conformance inspection, part 2</u>								
(B) 1316	Amplification factor	-	Ck = 1,000 μ F	---	---	Mu	40	90	---
(B) 1256	Electrode current (anode)	-		---	---	Ib	11.0	22.0	mAdc
(B) 1331	Direct-interelectrode capacitance	8		---	---	{ Cgp Cin Cout	0.85 1.5 ---	1.25 2.7 0.026	pF pF pF
1031	Low-frequency vibration	3	Ebb = 150 Vdc; Ec = 0; Ck = 1,000 μ F; Rp = 10,000 ohms; 15 G; F = 40 Hz	---	---	Ep	---	10	mVac
	<u>Quality conformance inspection, part 3</u>								
1506	Heater-cycling life	4	Ef = 7.0 V; Ehk = +70 Vdc; no other voltages applied	---	---	Cycles	2,000	---	---
---	Heater-cycling life test end point:								
1336	Heater-cathode leakage	-		---	---	Ihk	---	40	μ Adc
---	Life test	5, 7	Group A; Ef = 6.3 Vac, filament standby; no other voltages applied; t = 100 hours	---	---	---	---	---	---
---	Life-test end point	5		---	---	Δ ib	---	25	%


NOTES:

1. For purpose of achieving a faster warmup, a momentary elevated heater voltage up to 12 V may be used provided the duration does not exceed 1.0 second.
2. Cathode warmup is defined as the time in seconds required for the cathode current to attain 90 percent of the normally stabilized value at 6.0 seconds.
 - a. Conditions: Use grid pulse voltage test conditions (except E_f) including the grid pulse amplitude ($egy/ip = 1.2a$) previously determined.
 - b. Procedure: With the specified anode and grid voltages applied to the TUT, a heater voltage of 12.0 ± 0.5 Vdc shall be switched "ON" at "to". At "to +0.75" ± 0.05 seconds, the E_f shall be automatically switched to 6.4 ± 0.1 Vdc. An X-Y recording of the cathode current rise versus time shall be made on individual tubes. The i_k level at "to +0.75" seconds shall be at least 90 percent of the "to +6.0" second value.
3. The tube shall be vibrated with simple harmonic motion in each of two planes, (1) parallel to the cylindrical axis and (2) perpendicular to the cylindrical axis and parallel to a plane through the heater pins.
4. Sampling procedure and acceptance criteria for this test shall be as follows: Sample (n1) shall consist of 4 tubes with an acceptance number (c1) of zero. Electrical rejects other than inoperatives and heater-cathode defects may be used in performance of this test.
5. At zero hours, establish the drive conditions necessary to obtain 0.6 a peak anode current with an anode voltage of 400 Vdc and a bias voltage of -20 Vdc. The pulse width of the modulator shall be 1 μ s and the duty cycle shall be 0.001 (nominal). With the drive level determined at zero hours, check the anode current at the end-of-life. The maximum allowable drop in anode current (Δi_b) is 25 percent.
6. Test shall be performed as specified in method 1031, except that the tubes shall be vibrated for a total of 6 hours that is, 3 hours in each of two directions; first, parallel to the cylindrical axis; second, perpendicular to the cylindrical axis and perpendicular to a line through the heater pins.
7. The filament voltage shall be cycled on 1 hour 45 minutes and off 15 minutes. The specified life-test duration applies to accumulated on time.
- ⑧ 8. The TUT's acceptance and rejection criteria for this test shall be based on 100 percent inspection with no failures permitted.

Preparing activity:
Army - ER


Agent:
DLA - ES

(Project 5960-A165)



NOTE: Tube shall be so aligned that it is capable of being inserted into the alignment gage as shown on figure 2 and rotated 360 degrees without binding.

FIGURE 1. Outline drawing of electron tube type DOD-038.



NOTES:

- Dimensions are in inches.
- Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
- Tolerances of all gage dimensions are $\pm .001$ (.03 mm) unless otherwise specified.

FIGURE 2. Alignment gage.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLENegative Grid (Microwave), Type DOD-038MIL-E-1/1764B(ER), Electron Tube,**NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER**☐ **VENDOR** ☐ **USER** ☐ **MANUFACTURER**

1. ☐ **HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?** ☐ **IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.**

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS**SUBMITTED BY (Printed or typed name and address — Optional)****TELEPHONE NO.****DATE****DD FORM 1426**
1 OCT 76

EDITION OF 1 JAN 72 MAY BE USED UNTIL EXHAUSTED