



DEFENSE LOGISTICS AGENCY
WEAPONS SUPPORT
P.O. BOX 3990
COLUMBUS, OHIO 43218-3990

April 22, 2025

MEMORANDUM FOR MILITARY/INDUSTRY DISTRIBUTION

SUBJECT: Initial Draft of Performance Specification Sheet MIL-PRF-19500/746Dam5,
Project Number 5961-2026-044.

The initial draft for this subject document, dated April 22, 2025, is now available for viewing and downloading from the DLA Weapons Support-VA Web site:

<https://LandandMaritimeApps.dla.mil/Programs/MilSpec/DocSearch.aspx>

The initial draft of the subject document was generated to add an additional die version and to update it to the latest document format and various editorial changes to bring it into compliance with MIL-STD-961. Highlighting has been used for easy change recognition.

Concurrence or comments are required at this Center within 30 days from the date of this letter (May 22, 2025). Late comments will be held for the next coordination of the document. Comments from military departments must be identified as either "Essential" or "Suggested". Essential comments must be justified with supporting data. Military review activities should forward comments to their custodians of this office, as applicable, in sufficient time to allow for consolidating the department reply.

The point of contact for this document is Mr. Jason Hochstetler, DLA Weapons Support - VAC, Post Office Box 3990, Columbus, OH 43218-3990. Mr. Hochstetler can also be reached at 614-693-2825 / DSN 392-693-2825 or by e-mail to: Jason.hochstetler@dlamail.mil.

/ Signed /

MUHAMMAD AKBAR
Chief
Active Devices Branch

NOTE: This draft, dated 22 April 2026 prepared by DLA – CC, has not been approved and is subject to modification. DO NOT USE PRIOR TO APPROVAL.
(Project 5961-2026-044)
COMMENTS ARE DUE BY 22 May 2026.
P.O.C. Jason Hochstetler, ph 614-693-2825
e-mail: jason.hochstetler@dla.mil

INCH-POUND

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT
SUPERSEDING
MIL-PRF-19500/746D
w/AMENDMENT 4
11 August 2025

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, FIELD EFFECT, RADIATION HARDENED, N-CHANNEL, SILICON,
SURFACE MOUNT AND UN-ENCAPSULATED, TYPES 2N7587, 2N7589, 2N7591, AND 2N7593,
QUALITY LEVELS JANTXV, JANS, JANHC, AND JANKC

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of
this specification sheet and [MIL-PRF-19500](#).

1. SCOPE

1.1 Scope. This specification covers the performance requirements for a N-channel, enhancement-mode, MOSFET, radiation hardened (total dose and single event effects (SEE)), power transistor. Two levels of product assurance (JANTXV and JANS) are provided for each encapsulated device. Two levels of product assurance (JANHC and JANKC) are provided for each unencapsulated device. Three levels (R, F and G) of radiation hardness assurance (RHA) are provided for product assurance levels JANTXV, JANS, JANHC, and JANKC.

1.2 Physical dimensions.

1.2.1 Package outlines. The device package outline is a TO-276AA in accordance with [figure 1](#) for all encapsulated device types.

* 1.2.2 Die dimensions and topography. The dimensions and topography for JANHC and JANKC unencapsulated die are in accordance with [figure 2](#) and [figure 3](#), and [figure 4](#).

1.3 Maximum ratings. Unless otherwise specified, $T_A = +25^\circ\text{C}$.

Type (1)	P_T (2) $T_C = +25^\circ\text{C}$	P_T $T_A = +25^\circ\text{C}$	$R_{\theta JC}$ (3)	V_{DS}	V_{DG}	V_{GS}	I_{D1} (4) (5) $T_C = +25^\circ\text{C}$	I_{D2} $T_C = +100^\circ\text{C}$	I_S	I_{DM} (6)	T_J and T_{STG}	V_{ISO} 70,000 ft. altitude
	<u>W</u>	<u>W</u>	<u>$^\circ\text{C/W}$</u>	<u>V dc</u>	<u>V dc</u>	<u>V dc</u>	<u>A dc</u>	<u>A dc</u>	<u>A dc</u>	<u>A (pk)</u>	<u>$^\circ\text{C}$</u>	<u>V dc</u>
2N7587	75	1.56	1.67	100	100	± 20	22	19	22	88	-55	
2N7589	75	1.56	1.67	150	150	± 20	19	12	19	76	to	
2N7591	75	1.56	1.67	200	200	± 20	16	10	16	64	+150	
2N7593	75	1.56	1.67	250	250	± 20	12.4	7.8	12.4	49.6		250

- (1) Also applies to U3 and U3C suffix versions.
(2) Derate linearly by 0.6 W/ $^\circ\text{C}$ for $T_C > +25^\circ\text{C}$.
(3) See [figure 4](#), thermal impedance curves.

Comments, suggestions, or questions on this document should be addressed to DLA [Land and Maritime Weapons Support](#), ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at <https://assist.dla.mil>.

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

FSC 5961



MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

1.3 Maximum ratings – continued.

- (4) The following formula derives the maximum theoretical I_D limit. I_D is limited by package and internal wires and may be limited by pin diameter:
- $$I_D = \sqrt{\frac{T_{JM} - T_C}{(R_{\theta JC}) \times (R_{DS(on)} \text{ at } T_{JM})}}$$
- (5) See [figure 5](#) [figure 6](#), maximum drain current graph.
- (6) $I_{DM} = 4 \times I_{D1}$; I_{D1} as calculated by footnote (4).

1.4 Primary electrical characteristics. Unless otherwise specified at $T_C = +25^\circ\text{C}$.

Types (1)	Min $V_{(BR)DSS}$ $V_{GS} = 0$ $I_D = 1.0\text{mA dc}$	$V_{GS(TH)1}$ $V_{DS} \geq V_{GS}$ $I_D = 1.0 \text{ mA dc}$	Max I_{DSS1} $V_{GS} = 0$ $V_{DS} = 80\%$ of rated V_{DS}	Max $r_{DS(on)}$ (2) $V_{GS} = 12\text{V},$ $I_D = I_{D2}$	Max $r_{DS(on)}$ (2) $V_{GS} = 12\text{V},$ $I_D = I_{D2}$	E_{AS}
				$T_J = +25^\circ\text{C}$	$T_J = +150^\circ\text{C}$	
	<u>V dc</u>	<u>V dc</u> <u>Min</u> <u>Max</u>		<u>$\mu\text{A dc}$</u>	<u>Ω</u>	<u>mJ</u>
2N7587	100	2.0	4.0	10	0.042	73
2N7589	150	2.0	4.0	10	0.088	60
2N7591	200	2.0	4.0	10	0.130	60
2N7593	250	2.0	4.0	10	0.210	56

- (1) Also applies to U3 and U3C suffix versions.
- (2) Pulsed (see [4.5.1](#)).

1.5 Part or Identifying Number (PIN). The PIN is in accordance with [MIL-PRF-19500](#), and as specified herein. See [6.4](#) for PIN construction example and [6.5](#) for a list of available PINs.

1.5.1 JAN certification mark and quality level.

1.5.1.1 Quality level designators for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet are as follows: "JANTXV" and "JANS".

1.5.1.2 Quality level designators for un-encapsulated devices (die). The quality level designators for un-encapsulated devices that are applicable for this specification sheet are as follows: "JANH C" and "JANKC".

1.5.2 Radiation hardness assurance (RHA) designator. The RHA levels that are applicable for this specification sheet for product assurance levels JANTXV, JANS, JANHC, and JANKC from lowest to highest are as follows: "R", "F" and "G". See [1.6](#) for RHA details.

1.5.3 Device type. The designation system for the device types of transistors covered by this specification sheet are as follows.

1.5.3.1 First number and first letter symbols. The transistors of this specification sheet use the first number and letter symbols "2N".

1.5.3.2 Second number symbols. The second number symbols for the transistors covered by this specification sheet are as follows: "7587", "7589", "7591", and "7593".

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

1.5.4 Suffix letters. The following suffix letters are incorporated in the PIN for this specification sheet:

U3	Indicates a metal lidded 3 pad surface mount package similar to a TO-276AA (SMD-0.5) (see figure 1).
U3C	Indicates a ceramic lidded 3 pad surface mount package similar to a TO-276AA (SMD-0.5) (see figure 1).

1.5.5 Lead finish. The lead finishes applicable to this specification sheet are listed on [QPDSIS-19500](#).

* 1.5.6 Die identifiers for un-encapsulated devices (manufacturers and critical interface identifiers). The manufacturer die identifier that is applicable for this specification sheet is "A", [and "B"](#), [and "C"](#) (see [figure 2](#), [figure 3](#), [figure 4](#), and [6.5](#)).

1.6 Radiation features. The following radiation features are applicable for RHA devices supplied to this specification sheet.

1.6.1 Maximum total ionizing dose (TID). The maximum TID available in accordance with test method 1019 , condition A (dose rate = 50 to 300 rad(Si)/s) of [MIL-STD-750](#) are as follows:

For device types 2N7587U3, 2N7589U3, 2N7591U3: 300 krad(Si) 1/
 For device types 2N7587U3C, 2N7589U3C, 2N7591U3C: 300 krad(Si) 1/
 For device type 2N7593U3: 500 krad(Si) 1/

1.6.2 Heavy ion irradiation SEE. SEE testing includes Single-Event Burnout (SEB) and Single-Event Gate Rupture (SEGR) tests at the specified linear energy transfer (LET) units. See [6.7](#) for the specific RHA SEE characterization testing details. The following characterization conditions were used for the testing to the requirements herein:

For device type 2N7587:
 No SEB and SEGR were observed at surface LET (see [table IV](#)) $\leq 90 \text{ MeV} \cdot \text{cm}^2/\text{mg}$ 2/
 (In-situ Bias $V_{DS} = 100 \text{ V}$ and $V_{GS} = -5 \text{ V}$)

For device type 2N7589:
 No SEB and SEGR were observed at surface LET (see [table IV](#)) $\leq 90 \text{ MeV} \cdot \text{cm}^2/\text{mg}$ 2/
 (In-situ Bias $V_{DS} = 50 \text{ V}$ and $V_{GS} = -5 \text{ V}$)
 (In-situ Bias $V_{DS} = 30 \text{ V}$ and $V_{GS} = -10 \text{ V}$)

For device type 2N7591:
 No SEB and SEGR were observed at surface LET (see [table IV](#)) $\leq 90 \text{ MeV} \cdot \text{cm}^2/\text{mg}$ 2/
 (In-situ Bias $V_{DS} = 150 \text{ V}$ and $V_{GS} = -4 \text{ V}$)
 (In-situ Bias $V_{DS} = 110 \text{ V}$ and $V_{GS} = -5 \text{ V}$)

For device type 2N7593:
 No SEB and SEGR were observed at surface LET (see [table IV](#)) $\leq 90 \text{ MeV} \cdot \text{cm}^2/\text{mg}$ 2/
 (In-situ Bias $V_{DS} = 250 \text{ V}$ and $V_{GS} = -5 \text{ V}$)

- 1/ The manufacturers supplying these device types have performed characterization testing in accordance with condition A (dose rate = 50 to 300 rad(Si)/s) of method 1019 of [MIL-STD-750](#). The radiation end point limits are guaranteed only to a maximum TID level of 300 krad(Si) and 500 krad(Si).
- 2/ The manufacturers have performed SEE tests at Texas A&M University (TAMU) Radiation Effects Facility in accordance with method 1080 of [MIL-STD-750](#). For more information on SEE testing and results, customers should contact the qualified manufacturer.

Technical drawing of a rectangular plate with dimensions and tolerances. The drawing includes a top view and a side view. The top view shows a rectangle with width BL and height BW. The side view shows a plate with thickness CH. The drawing includes a table with the following data:


Feature	Value	Unit	Material	Surface	Finish
Top Surface	0.10	(0.004)	C	A	M
Bottom Surface	0.10	(0.004)	C	A	M
Left Surface	0.10	(0.004)	C	A	M
Right Surface	0.10	(0.004)	C	A	M
Front Surface	0.10	(0.004)	C	A	M
Back Surface	0.10	(0.004)	C	A	M

Symbol	Dimensions				Symbol	Dimensions			
	Inches	Inches	mm	mm		Inches	Inches	mm	mm
	Min	Max	Min	Max		Min	Max	Min	Max
BL	.395	.405	10.03	10.29	LS1	.150 BSC		3.81 BSC	
BW	.291	.301	7.39	7.65	LS2	.075 BSC		1.91 BSC	
CH (for U3)	.108	.124	2.74	3.15	LW1	.281	.291	7.14	7.39
CH (for U3C)		.1335		3.39	LW2	.090	.100	2.29	2.54
LH	.010	.020	0.25	0.51	Q1	.030		0.76	
LL1	.220	.230	5.59	5.84	Q2	.030		0.76	
LL2	.115	.125	2.92	3.18					

1. Dimensions are in inches. Millimeters are given for information only.
2. Terminal 1 is the drain, terminal 2 is the gate, and terminal 3 is the source.
3. The following suffixes apply to this package configuration: Metal lid: U3 suffix; Ceramic lid: U3C suffix.
4. The lid shall be electrically isolated from the drain, gate, and source.

4

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026




Key	Dimensions					
	Inches	Inches	Micrometers	Micrometers	Tolerance	Tolerance
	X	Y	X	Y	Inches	μmeter
1	0	0	0	0	±.0002	±5
2	0	.02129	0	541	±.0002	±5
3	.02119	0	538.3	0	±.0002	±5
4	.02119	.02129	538.3	541	±.0002	±5
5	.03570	.00303	906.8	77	±.0002	±5
6	.03570	.04606	906.8	1169.9	±.0002	±5
7	.15726	.00303	3994.5	77	±.0002	±5
8	.15726	.04606	3994.5	1169.9	±.0002	±5
A	.1815		4611		±.0079	±200
B	.1160		2946		±.0079	±200
C	.0074		187.9		N/A	N/A

NOTES:

1. Dimensions are in inches. Micrometers are given for general information only.
2. All dimensions are valid for all radiation hardness levels specified.
3. For sawn die, outline dimensions (A and B) will be reduced by .00098 inches (25 μm), due to saw kerf.
4. Die bond pad coordinates are provided for use in automated bonding equipment. Key locations 1 through 4 refer to adjacent gate (G) pad corners. Key locations 5 through 8 refer to adjacent source (S) pad corners.
5. Key 2 through 8 are relative to Key 1.
6. Top metal: Aluminum, 56,000 Å thick.
7. Back metal: Aluminum, Titanium, nickel, silver 1000 Å, 1000 Å, 4000 Å, 6000 Å thick, respectively.
8. Backside metal is the drain connection.

FIGURE 2. JANHC and JANKC (A-version) die dimensions.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026




Key	Dimensions					
	Inches	Inches	Micrometers	Micrometers	Tolerance	Tolerance
	X	Y	X	Y	Inches	μmeter
1	0	0	0	0	± 0.0002	± 5
2	0.01504	0	382	0	± 0.0002	± 5
3	0	0.01657	0	421	± 0.0002	± 5
4	0.01504	0.01657	382	421	± 0.0002	± 5
5	0.02055	0.06040	522	1534.2	± 0.0002	± 5
6	0.03559	0.06040	904	1534.2	± 0.0002	± 5
7	0.02055	0.10631	522	2700.2	± 0.0002	± 5
8	0.03559	0.10631	904	2700.2	± 0.0002	± 5
A	0.1843		4682		± 0.0079	± 200
B	0.1543		3920		± 0.0079	± 200
C	0.0150		381		± 0.0010	± 25

NOTES:

1. Dimensions are in inches. Micrometers are given for general information only.
2. All dimensions are valid for all radiation hardness levels specified.
3. For sawn die, outline dimensions (A and B) will be reduced by 0.001 inches (25 μm), due to saw kerf.
4. Die bond pad coordinates are provided for use in automated bonding equipment. Key locations 1 through 4 refer to adjacent gate (G) pad corners. Key locations 5 through 8 refer to adjacent source (S) pad corners.
5. Key 2 through 8 are relative to Key 1.
6. Top metal: 150V and 250V - Aluminum Copper (0.5%) Silicon (1%), 55,000 Å
7. Back metal: Titanium, Nickel, Silver 700 Å, 3200 Å, 7500 Å thick, respectively
8. Backside metal is the drain connection.

FIGURE 3. JANHC and JANKC (B-version) die dimensions.



Ltr	Dimensions 2N7587, 2N7589, 2N7591, 2N7593			
	Inches		Millimeters	
	Min	Max	Min	Max
A	0.120	0.130	3.05	3.30
B	0.175	0.185	4.44	4.70
C	0.089	0.099	2.26	2.51
D	0.020	0.026	0.51	0.66
E	0.133	0.143	3.38	3.63
F	0.009	0.013	0.23	0.33
G	0.012	0.016	0.30	0.41

NOTES:

1. Dimensions are in inches. Millimeters are given for general information only.
2. Die thickness = .014 ± .003 inch (0.36 ± 0.07 mm).
3. Back metal: Titanium 1.15KÅ, Nickel 2KÅ, and Silver 8KÅ. Nominal.
4. Top metal: Al 40KÅ. Nominal.
5. Back contact: Drain.

* FIGURE 4. JANHCC and JANKCC (C-version) die dimensions for 2N7587, 2N7589, 2N7591, 2N7593.

* 2. APPLICABLE DOCUMENTS PUBLICATIONS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 – Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 – Test Methods For Semiconductor Devices.
MIL-STD-883 – Test Method Standard for Microcircuits.

(Copies of these documents are available online at <https://quicksearch.dla.mil>).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

* 3.4 Interface requirements and physical dimensions. The interface requirements and physical dimensions shall be as specified in MIL-PRF-19500 and herein. The device package style is either a metal lidded or ceramic lidded TO-276AA in accordance with figure 1 for all encapsulated devices. See figure 2 and figure 3, and figure 4 for un-encapsulated JANHC and JANKC die.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4.2 Multiple chip construction. Multiple chip construction shall not be permitted in order to meet the requirements of this specification.

3.4.3 Pin-out. The pin-out of the device shall be as shown on figure 1.

3.4.4 Silicone die coating. The use of a silicone die coat requires a successful completion of method 5011 of MIL-STD-883, on each lot of silicone die coating for its intended applications.

3.5 Marking. Marking shall be in accordance with [MIL-PRF-19500](#).

3.6 Electrostatic discharge sensitive (ESDS). The devices covered by this specification sheet have been classified as ESDS. The devices shall be handled in accordance with the ESD program established to comply with the requirements of [MIL-PRF-19500](#) to avoid damage due to the accumulation of static charge. The following handling practices shall be followed:

- a. Devices should be handled on benches with conductive handling devices.
- b. Ground test equipment, tools, and personnel handling devices.
- c. Do not handle devices by the leads.
- d. Store devices in conductive foam or carriers.
- e. Avoid use of plastic, rubber or silk in MOS areas.
- f. Maintain relative humidity above 50 percent if practical.
- g. Care should be exercised during test and troubleshooting to apply not more than maximum rated voltage to any lead.
- h. Gate must be terminated to source, $R \leq 100 \text{ k}\Omega$, whenever bias voltage is applied drain to source.

3.7 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in [1.3](#), [1.4](#), and [table I](#).

3.8 RHA. RHA requirements and test levels shall be as defined in [MIL-PRF-19500](#) and herein. RHA characterization data shall be made available upon request of the acquiring or qualifying activity.

3.8.1 SEE. After being tested for SEE as specified in [4.5.2](#) at the identified test location (see [6.7](#)) using the exposure, beam and bias conditions listed in [table IV](#), the device testing conditions shall be listed in [table IV](#).

3.9 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

- a. Qualification inspection (see [4.2](#)).
- b. Screening (see [4.3](#)).
- c. Conformance inspection (see [4.4](#) and [tables I](#), and [II](#)).
- d. Element evaluation of un-encapsulated die (see [4.6](#)).

4.2 Qualification inspection. Qualification inspection shall be in accordance with [MIL-PRF-19500](#) and as specified herein.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of [table III](#) tests, the tests specified in [table III](#) herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

4.2.2 SEE. SEE (SEB/SEGR) shall be performed at initial qualification and thereafter whenever a process or a major die design change which may affect radiation hardness is introduced. Upon qualification, manufacturers shall provide the SEE verification test conditions from section 5 of method 1080 of [MIL-STD-750](#) that were used to qualify the device for inclusion into section 6 herein.

4.2.3 Silicone die coating. The successful completion of method 5011 of [MIL-STD-883](#) on silicone die coating shall be part of the full [MIL-PRF-19500](#) qualification process.

4.3 Screening of encapsulated devices. Screening of packaged devices shall be in accordance with table E-IV of [MIL-PRF-19500](#), and as specified herein. The following measurements shall be made in accordance with [table I](#) herein. Devices that exceed the limits of [table I](#) herein shall not be acceptable.

Screen (1) (2)	Measurements for JANS	Measurements for JANTXV
(3)	Gate stress test (see 4.3.1)	Gate stress test (see 4.3.1)
(3)	Method 3470 of MIL-STD-750 , E _{AS} (see 4.3.2)	Method 3470 of MIL-STD-750 , E _{AS} (see 4.3.2)
(3) 3c	Method 3161 of MIL-STD-750 , thermal impedance, (see 4.3.3)	Method 3161 of MIL-STD-750 , thermal impedance, (see 4.3.3)
5	Method 2052 of MIL-STD-750 , PIND (see 4.3.4)	Not applicable
9	Subgroup 2 of table I herein	Not applicable
10	Method 1042 of MIL-STD-750 , test condition B	Method 1042 of MIL-STD-750 , test condition B
11	Subgroup 2 of table I herein. $\Delta I_{GSSF1} = \pm 20$ nA dc or ± 100 percent of initial value, whichever is greater. $\Delta I_{GSSR1} = \pm 20$ nA dc or ± 100 percent of initial value, whichever is greater. $\Delta I_{DSS1} = \pm 10$ μ A dc or ± 100 percent of initial value, whichever is greater.	Subgroup 2 of table I herein.
12	Method 1042 of MIL-STD-750 , test condition A	Method 1042 of MIL-STD-750 , test condition A
13	Subgroups 2 and 3 of table I herein $\Delta I_{GSSF1} = \pm 20$ nA dc or ± 100 percent of initial value, whichever is greater. $\Delta I_{GSSR1} = \pm 20$ nA dc or ± 100 percent of initial value, whichever is greater. $\Delta I_{DSS1} = \pm 10$ μ A dc or ± 100 percent of initial value, whichever is greater. $\Delta r_{DS(ON)1} = \pm 20$ percent of initial value. $\Delta V_{GS(TH)1} = \pm 20$ percent of initial value.	Subgroup 2 of table I herein $\Delta I_{GSSF1} = \pm 20$ nA dc or ± 100 percent of initial value, whichever is greater. $\Delta I_{GSSR1} = \pm 20$ nA dc or ± 100 percent of initial value, whichever is greater. $\Delta I_{DSS1} = \pm 10$ μ A dc or ± 100 percent of initial value, whichever is greater. $\Delta r_{DS(ON)1} = \pm 20$ percent of initial value. $\Delta V_{GS(TH)1} = \pm 20$ percent of initial value.
17	For TO-276AA packages: Method 1081 of MIL-STD-750 , DWV (see 4.3.5), Endpoints: Subgroup 2 of table I herein.	For TO-276AA packages: Method 1081 of MIL-STD-750 , DWV (see 4.3.5), Endpoints: Subgroup 2 of table I herein.

- (1) At the end of the test program, I_{GSSF1} , I_{GSSR1} , and I_{DSS1} are measured.
- (2) An out-of-family program to characterize I_{GSSF1} , I_{GSSR1} , I_{DSS1} and $V_{GS(th)1}$ shall be invoked.
- (3) Shall be performed anytime after temperature cycling, screen 3a; JANTXV does not need to be repeated in screening requirements.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

4.3.1 Gate stress test. Apply $V_{GS} = 24$ V minimum for $t = 250$ μ s minimum.

4.3.2 Single pulse avalanche energy (E_{AS}). The test for single pulse avalanche energy shall be performed in accordance with method 3470 of [MIL-STD-750](#). The following details shall apply:

- a. Peak current (I_{AS})..... $I_{AS} = I_{D1}$.
- b. Inductance (L)..... $L = \left[\frac{2E_{AS}}{(I_{D1})^2} \right] \left[\frac{V_{BR} - V_{DD}}{V_{BR}} \right]$ mH minimum.
- c. Gate to source resistor (R_{GS}) $25 \leq R_{GS} \leq 200 \Omega$.
- d. Supply voltage (V_{DD}) $V_{DD} = 25$ V dc, except $V_{DD} = 50$ V dc (2N7593), up to rated V_{DS} .
- e. Peak gate voltage (V_{GS})..... 12 V, up to maximum rated V_{GS} .
- f. Initial case temperature (T_C) $T_C = +25^\circ\text{C}$, $+10^\circ\text{C}$, -5°C .
- g. Number of pulses to be applied 1 pulse minimum.

4.3.3 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3161 of [MIL-STD-750](#) using the guidelines in that method for determining I_M , I_H , t_H , t_{SW} , t_{MD} (and V_H where appropriate). See [table III](#), group E, subgroup 4 herein.

4.3.4 PIND. Not applicable in screening when devices are processed using alternative method and flow requirements approved by the qualifying activity, that includes incorporating the use of certified clean processing and silicone die coat. Instead, the PIND test performance shall be performed in group B3 and group C3, on a lot sample basis. PIND failures detected in group B or C will represent lot jeopardy and be evaluated for root cause and lot integrity.

4.3.5 Dielectric withstanding voltage (DWV). The test for DWV shall be performed in accordance with test method 1081 of [MIL-STD-750](#). The following details shall apply:

- a. Magnitude of test voltage.....600V dc.
- b. Duration of application of test voltage 15 seconds (min).
- c. Points of application of test voltage All leads to case (bunch connection).
- d. Method of connection.....Mechanical.
- e. Kilovolt-ampere rating of high voltage source 1,200 V, 1.0 mA (min).
- f. Maximum leakage current.....1.0 mA.
- g. Voltage ramp up time.....500 V/second.

4.4 Conformance inspection. Conformance inspection shall be in accordance with [MIL-PRF-19500](#) and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table E-V of [MIL-PRF-19500](#) and [table I](#) herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIA (JANS) and table E-VIB (JANTXV) of [MIL-PRF-19500](#), and as follows.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

4.4.2.1 Quality level JANS (table E-VIA of [MIL-PRF-19500](#)).

<u>Subgroup</u>	<u>Method</u>	<u>Condition</u>
B3	1051	Test condition G, 100 cycles.
B3	2077	Scanning electron microscope (SEM).
B3	2052	PIND, required if not performed in screening. Sampling plan 22 devices, c = 0 for large lots, 12 devices, c = 0 for small lots.
B4	1042	Intermittent operation life, condition D, t_{on} shall be 30 seconds minimum.
B5	1042	Accelerated steady-state gate bias, condition B, V_{GS} = rated V_{GS} ; T_A = +175 °C, t = 24 hours minimum; or T_A = +150 °C, t = 48 hours minimum.
B5	1042	Accelerated steady-state reverse bias, condition A, V_{DS} = rated V_{DS} ; T_A = +175 °C, t = 120 hours minimum; or T_A = +150 °C, t = 240 hours minimum.
B5	2037	Test condition D.

4.4.2.2 Quality level JANTXV (table E-VIB of [MIL-PRF-19500](#)).

<u>Subgroup</u>	<u>Method</u>	<u>Condition</u>
B2	1051	Test condition G, 25 cycles.
B3	1042	Intermittent operation life, condition D, t_{on} shall be 30 seconds minimum.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of [MIL-PRF-19500](#) and as follows.

<u>Subgroup</u>	<u>Method</u>	<u>Condition</u>
C2	2036	Terminal strength is not applicable.
C3	2052	PIND, required if not performed in screening. Sampling plan 22 devices, c = 0 for large lots, 12 devices, c = 0 for small lots.
C5	3161	See 4.3.3, $R_{\theta JC}$ = 1.67 °C/W.
C6	1042	Intermittent operation life, condition D, t_{on} shall be 30 seconds minimum.

4.4.4 Group D inspection. Group D inspection shall be conducted in accordance with table E-VIII of [MIL-PRF-19500](#) and [table II](#) herein.

4.4.5 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of [MIL-PRF-19500](#) and as specified in [table III](#) herein.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of [MIL-STD-750](#).

4.5.2 SEE. The heavy ion SEE (SEB/SEGR) characterization testing shall be performed in accordance with method 1080 of [MIL-STD-750](#). Electrical measurements (end-points) shall be in accordance with [table III](#) herein.

4.6 Element evaluation of un-encapsulated die. The element evaluation of un-encapsulated die shall be in accordance with appendix G of [MIL-PRF-19500](#).

TABLE I. Group A inspection.

Inspection 1/ , 2/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Condition		Min	Max	
<u>Subgroup 1</u>						
Visual and mechanical examination	2071					
<u>Subgroup 2</u>						
Thermal impedance 3/	3161	See 4.3.3	$Z_{\theta JC}$			°C/W
Breakdown voltage drain to source	3407	Bias condition C, $V_{GS} = 0$ V, $I_D = 1$ mA dc	$V_{(BR)DSS}$	100 150 200 250		V dc V dc V dc V dc
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS}$, $I_D = 1$ mA dc	$V_{GS(TH)1}$	2.0	4.0	V dc
Gate current	3411	Bias condition C, $V_{GS} = +20$ V dc, $V_{DS} = 0$ V	I_{GSSF1}		+100	nA dc
Gate current	3411	Bias condition C, $V_{GS} = -20$ V dc, $V_{DS} = 0$ V	I_{GSSR1}		-100	nA dc
Drain current	3413	Bias condition C, $V_{GS} = 0$ V dc, $V_{DS} = 80$ percent of rated V_{DS}	I_{DSS1}		10	μA dc

See footnotes at end of table.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

TABLE I. Group A inspection - Continued.

Inspection <u>1/</u> , <u>2/</u>	MIL-STD-750		Symbol	Limits		Unit
	Method	Condition		Min	Max	
<u>Subgroup 2</u> - continued.						
Static drain to source on-state resistance 2N7587 2N7589 2N7591 2N7593	3421	Condition A, $V_{GS} = 12$ V dc, pulsed (see 4.5.1), $I_D = I_{D2}$	$r_{DS(ON)1}$		0.042 0.088 0.130 0.210	Ω Ω Ω Ω
Forward voltage	4011	Condition A, $V_{GS} = 0$ V dc, $I_D = I_{D1}$	V_{SD}		1.2	V dc
<u>Subgroup 3</u>						
High temperature operation		$T_C = T_J = +125^\circ\text{C}$				
Gate current	3411	Bias condition C, $V_{GS} = \pm 20$ V dc, $V_{DS} = 0$ V	I_{GSS2}		± 200	nA dc
Drain current	3413	Bias condition C, $V_{GS} = 0$ V dc, $V_{DS} = 80$ percent of rated V_{DS}	I_{DSS2}		25	μA dc
Static drain to source on-state resistance 2N7587 2N7589 2N7591 2N7593	3421	Condition A, $V_{GS} = 12$ V dc, pulsed (see 4.5.1), $I_D = I_{D2}$	$r_{DS(ON)3}$		0.080 0.176 0.273 0.441	Ω Ω Ω Ω
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS}$, $I_D = 1$ mA dc	$V_{GS(TH)2}$	1.0		V dc
Low temperature operation		$T_C = T_J = -55^\circ\text{C}$				
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS(TH)3}$, $I_D = 1$ mA dc	$V_{GS(TH)3}$		5.0	V dc
<u>Subgroup 4</u>						
Forward transconductance 2N7587 2N7589 2N7591 2N7593	3475	$I_D = I_{D2}$, $V_{DD} = 15$ V dc (see 4.5.1)	g_{FS}	14 13 10 8.8		S S S S

See footnotes at end of table.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

TABLE I. Group A inspection - Continued.

Inspection <u>1/</u> , <u>2/</u>	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Condition		Min	Max	
<u>Subgroup 4</u> - continued.						
Switching time test	3472	I_D = rated I_{D1} , V_{GS} = 12 V dc, R_G = 7.5 Ω , V_{DD} = 50 percent of rated V_{DS}	$t_{d(on)}$		25	ns
Turn-on delay time						
Rise-time						
Turn-off delay time						
Fall time						
<u>Subgroup 5</u>						
Safe operating area	3474	See <u>figure 6</u> <u>figure 7</u> ; t_p = 10 ms min. V_{DS} = 80 percent of max. rated V_{DS} See <u>table I</u> , subgroup 2				
Electrical measurements						
<u>Subgroup 6</u>						
Not applicable						
<u>Subgroup 7</u>						
Gate charge	3471	Condition B, I_D = I_{D1} , V_{GS} = 12 V dc V_{DD} = 50 percent of rated V_{DS}	$Q_{G(ON)}$ $Q_{G(OFF)}$		50 50	nC nC
On-state gate charge and turn-off gate charge						
Gate to source charge (turn-on and turn-off)						
Gate to drain charge (turn-on and turn-off)						
Reverse recovery time						
2N7587	3473	Condition A, di/dt = -100 A/ μ s, $V_{DD} \leq 50$ V, I_D = I_{D1}	t_{rr}		350	ns
2N7589						
2N7591						
2N7593						

1/ Also applies to U3 and U3C suffix versions.

2/ For sampling plan, see [MIL-PRF-19500](#).

3/ For end-point measurements, this test is required for the following subgroups:

Group B, subgroups 2 and 3 (JANTXV).

Group B, subgroups 3 and 4 (JANS).

Group C, subgroup 2 and 6.

Group E, subgroup 1.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

TABLE II. Group D inspection.

Inspection 1/ 2/ 3/	MIL-STD-750		Symbol	Pre-irradiation limits		Post-irradiation limits		Unit
	Method	Conditions		R, F, G	R, F, G	R, F, G	R, F, G	
				Min	Max	Min	Max	
Subgroup 1								
Not applicable								
Subgroup 2		T _C = + 25 °C						
Steady-state total dose irradiation (V _{GS} bias) 4/	1019	Condition A, V _{GS} = 12 V; V _{DS} = 0						
Steady-state total dose irradiation (V _{DS} bias) 4/	1019	Condition A, V _{GS} = 0; V _{DS} = 80 percent of rated V _{DS} (pre-irradiation)						
End-point electricals								
Breakdown voltage, drain to source	3407	Bias condition C, V _{GS} = 0; I _D = 1 mA	V _{(BR)DSS}					
2N7587				100		100		V dc
2N7589				150		150		V dc
2N7591				200		200		V dc
2N7593				250		250		V dc
Gate to source voltage (threshold)	3403	V _{DS} ≥ V _{GS} , I _D = 1 mA	V _{GS(th)1}	2.0	4.0	2.0	4.0	V dc
Gate current	3411	Bias condition C, V _{GS} = +20 V; V _{DS} = 0	I _{GSSF1}		100		100	nA dc
Gate current	3411	Bias condition C, V _{GS} = -20 V; V _{DS} = 0	I _{GSSR1}		-100		-100	nA dc
Drain current	3413	Bias condition C, V _{GS} = 0, V _{DS} = 80 percent of rated V _{DS} (pre-irradiation)	I _{DSS}		10		10	µA dc
Static drain to source on-state voltage	3405	V _{GS} = 12 V; I _D = I _{D2} condition A, pulsed (see 4.5.1)	V _{DS(on)}					
2N7587					0.855		0.855	V dc
2N7589					1.104		1.104	V dc
2N7591					1.340		1.340	V dc
2N7593					1.638		1.638	V dc
Forward voltage source drain diode	4011	Bias condition A, V _{GS} = 0; I _D = I _{D1}	V _{SD}		1.2		1.2	V dc

- 1/ For sampling plan, see [MIL-PRF-19500](#). Characteristics also apply to U3 and U3C suffix versions.
- 2/ Group D qualification may be performed prior to lot formation. Wafers qualified to these group D QCI requirements may be used for any other specification sheets utilizing the same die design.
- 3/ At the manufacturer's option, group D samples need not be subjected to the screening tests and may be assembled in its qualified package or in any qualified package that the manufacturer has data to correlate the performance to the designated package.
- 4/ Separate samples shall be selected for each bias. Devices supplied to this specification sheet have been characterized through RHA levels R and F of irradiation. Pre and Post irradiation values are identical unless otherwise specified in [table II](#). When performing post irradiation electrical measurements for any RHA level, $T_A = +25^{\circ}\text{C}$ (see [1.6](#) herein).

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

TABLE III. Group E inspection (all quality levels) for qualification or re-qualification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
<u>Subgroup 1</u>			45 devices, c = 0
Temperature cycling	1051	Test condition G, 500 cycles.	
Hermetic seal	1071	Fine and gross leak, as applicable.	
Electrical measurements		See table I , subgroup 2 herein.	
<u>Subgroup 2</u> ^{1/}			45 devices, c = 0
Steady-state gate bias	1042	Condition B, 1,000 hours.	
Electrical measurements		See table I , subgroup 2 herein.	
Steady-state reverse bias	1042	Condition A, 1,000 hours.	
Electrical measurements		See table I , subgroup 2 herein.	
<u>Subgroup 4</u>			Sample size, N/A
Thermal impedance curves		See MIL-PRF-19500 .	
<u>Subgroup 5</u>			
Barometric pressure	1001	Condition C (to 70,000 feet).	3 devices, c = 0
<u>Subgroup 10</u>			22 devices, c = 0
Commutating diode for safe operating area	3476	Test conditions shall be derived by the manufacturer.	
<u>Subgroup 11</u>			3 devices
SEE ^{2/} ^{3/}	1080	See 1.6 , 6.2 , 6.7 , and table IV .	

^{1/} A separate sample for each test shall be selected.

^{2/} Group E qualification of SEE testing may be performed prior to lot formation. Qualification may be extended to other specification sheets utilizing the same structurally identical die design.

^{3/} Device qualification to a higher level LET is sufficient to qualify all lower level LETs.




FIGURE 4-5. Thermal response curve.





FIGURE 5 6. Maximum drain current versus case temperature graphs.

2N7587U3 and 2N7587U3C



2N7589U3 and 2N7589U3C





FIGURE 6 7. Safe operating area graph.

2N7591U3 and 2N7591U3C



2N7593U3 and 2N7593U3C




FIGURE 6 7. Safe operating area graph – Continued.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.


6.2 Acquisition requirements. Acquisition documents should specify the following:

- a. Title, number, and date of this specification.
- b. Packaging requirements (see 5.1).
- c. Lead finish (see 3.4.1).
- d. The complete PIN, see 1.5 and 6.4.
- e. For acquisition of JANHC or JANKC die, the die identifier letter version should be specified (see 1.5.6, 6.4.2, figure 2 and figure 3).
- f. For acquisition of RHA designated devices, table II, subgroup 1 testing of group D herein is optional. If subgroup 1 is desired, it should be specified in the contract.
- g. If specific SEE characterization conditions are desired (see section 6.7 and table IV), manufacturer's CAGE code should be specified in the contract or order.
- h. If SEE testing data is desired, it should be specified in the contract or order.


6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime Weapons Support, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at <https://qpldocs.dla.mil>.

6.4 PIN construction examples.

6.4.1 Encapsulated devices. The PINs for encapsulated devices are constructed using the following form.



6.4.2 Un-encapsulated devices. The PINs for un-encapsulated devices are constructed using the following form.



6.5 List of PINs.

6.5.1 List of PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

Quality level "TXV" 1/		Quality level "S" 1/		
JANTXVF2N7587U3	JANTXVR2N7587U3	JANSF2N7587U3	JANSR2N7587U3	
JANTXVF2N7587U3C	JANTXVR2N7587U3C	JANSF2N7587U3C	JANSR2N7587U3C	
JANTXVF2N7589U3	JANTXVR2N7589U3	JANSF2N7589U3	JANSR2N7589U3	
JANTXVF2N7589U3C	JANTXVR2N7589U3C	JANSF2N7589U3C	JANSR2N7589U3C	
JANTXVF2N7591U3	JANTXVR2N7591U3	JANSF2N7591U3	JANSR2N7591U3	
JANTXVF2N7591U3C	JANTXVR2N7591U3C	JANSF2N7591U3C	JANSR2N7591U3C	
JANTXVF2N7593U3	JANTXVR2N7593U3	JANSF2N7593U3	JANSR2N7593U3	JANSF2N7593U3
JANTXVF2N7593U3C	JANTXVR2N7593U3C	JANSF2N7593U3C	JANSR2N7593U3C	

These PIN are also available without a RHA designator.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

* 6.5.2 List of PINs for un-encapsulated devices. The following is a list of possible PINs available on this specification sheet. The qualified die suppliers with the applicable letter version (e.g., JANHCAR2N7587) will be identified on the QML.

Die ordering information			
Type	Manufacturer 1/	Manufacturer 1/	Manufacturer 1/
	69210	43611	52GC4
2N7587	JANHCA#2N7587 JANKCA#2N7587	JANHCB#2N7587 JANKCB#2N7587	JANHCC#2N7587 JANKCC#2N7587
2N7589	JANHCA#2N7589 JANKCA#2N7589	JANHCB#2N7589 JANKCB#2N7589	JANHCC#2N7589 JANKCC#2N7589
2N7591	JANHCA#2N7591 JANKCA#2N7591	JANHCB#2N7591 JANKCB#2N7591	JANHCC#2N7591 JANKCC#2N7591
2N7593	JANHCA#2N7593 JANKCA#2N7593	JANHCB#2N7593 JANKCB#2N7593	JANHCC#2N7593 JANKCC#2N7593

1/ The number sign (#) represent one of three RHA designators available (R, F, or G).
The PIN is also available without a RHA designator.

6.6 Substitution information. Devices covered by this specification are substitutable for the manufacturer's and user's PIN (without JAN and RHA prefix). This information in no way implies that manufacturer's PINs are substitutable for the military PIN.

Preferred military types	Commercial PIN	Commercial PIN
2N7587U3 2N7589U3 2N7591U3 2N7593U3	IRHNJ67130 IRHNJ67134 IRHNJ67230 IRHNJ67234	MRH15N19U3 MRH25N12U3
2N7587U3C 2N7589U3C 2N7591U3C 2N7593U3C	IRHNJC67130 IRHNJC67134 IRHNJC67230 IRHNJC67234	

6.7 Manufacturer specific SEE irradiation characterization conditions. The manufacturer's SEE irradiation characterization conditions listed in [table IV](#) is for information only. Each qualified manufacturer identified in [table IV](#) has characterized its devices to the requirements of method 1080 of [MIL-STD-750](#) using the testing conditions specified herein (see [1.6](#) and [table IV](#)). Since each manufacturer's characterization testing conditions can be different and may vary by the revision of method 1080 of [MIL-STD-750](#) that was used during qualification testing, the revision and conditions used by each manufacturer for characterization have been listed in [table IV](#) for information only.

The SEE (SEB and SEGR) conditions and figures listed herein are current of the date of this specification sheet. For irradiation testing results data, please contact the qualified manufacturer for the most recent conditions.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

TABLE IV. SEE characterization conditions for method 1080 of [MIL-STD-750. 1/](#)

Inspection	Type	Irradiation conditions
Applicable to manufacturer CAGE code 69210 only. 2/		
Sample size of 3 devices. Applicable to devices with a date code of September 2009 and newer.		
Pre SEE electrical measurements SEE 3/	All devices in sample	I_{GSSF1} , I_{GSSR1} , and I_{DSS1} in accordance with table I , subgroup 2 Fluence = $3 \times 10^5 \pm 20$ percent ions/cm ² Flux = 2×10^3 to 2×10^4 ions/cm ² /sec, temperature = $25 \pm 5^\circ\text{C}$
	2N7587	Surface LET = 39 MeV-cm ² /mg, range = 40 μm , Kr ion energy = 315 MeV In-situ bias conditions: $V_{DS} = 100\text{ V}$ and $V_{GS} = -19\text{ V}$; $V_{DS} = 40\text{ V}$ and $V_{GS} = -20\text{ V}$ (Typical 3.80 MeV/Nucleon at Texas A & M Cyclotron)
	2N7589	Surface LET = 39 MeV-cm ² /mg, range = 50 μm , Kr ion energy = 410 MeV In-situ bias conditions: $V_{DS} = 150\text{ V}$ and $V_{GS} = -20\text{ V}$ (Typical 4.90 MeV/Nucleon at Texas A & M Cyclotron)
	2N7591	Surface LET = 42 MeV-cm ² /mg, range = 205 μm , Kr ion energy = 2450 MeV In-situ bias conditions: $V_{DS} = 200\text{ V}$ and $V_{GS} = -10\text{ V}$; $V_{DS} = 190\text{ V}$ and $V_{GS} = -15\text{ V}$ (Typical 18.93 MeV/Nucleon at Texas A & M Cyclotron)
	2N7593	Surface LET = 44 MeV-cm ² /mg, range = 125 μm , Ag ion energy = 1350 MeV In-situ bias conditions: $V_{DS} = 250\text{ V}$ and $V_{GS} = -15\text{ V}$, $V_{DS} = 40\text{ V}$ and $V_{GS} = -20\text{ V}$ (Typical 10.05 MeV/Nucleon at Texas A & M Cyclotron)
Post SEE electrical measurements	All devices in sample	I_{GSSF1} , I_{GSSR1} , and I_{DSS1} in accordance with table I , subgroup 2

See footnotes at end of table.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

TABLE IV. SEE characterization conditions for method 1080 of MIL-STD-750 – Continued. 1/

Inspection	Type	Irradiation conditions
Applicable to manufacturer CAGE code 69210 only – continued. 2/		
Sample size of 3 devices. Applicable to devices with a date code of September 2009 and newer.		
Pre SEE electrical measurements SEE 3/	All devices in sample	I_{GSSF1} , I_{GSSR1} , and I_{DSS1} in accordance with table I, subgroup 2
		Fluence = $3 \times 10^5 \pm 20$ percent ions/cm ² Flux = 2×10^3 to 2×10^4 ions/cm ² /sec, temperature = $25 \pm 5^\circ\text{C}$
	2N7587	Surface LET = 61 MeV-cm ² /mg, range = 32 μm , Xe ion energy = 345 MeV In-situ bias conditions: $V_{DS} = 100\text{ V}$ and $V_{GS} = -10\text{ V}$; $V_{DS} = 30\text{ V}$ and $V_{GS} = -15\text{ V}$ (Typical 2.70 MeV/Nucleon at TAMU Cyclotron)
	2N7589	Surface LET = 61 MeV-cm ² /mg, range = 66 μm , Xe ion energy = 825 MeV In-situ bias conditions: $V_{DS} = 150\text{ V}$ and $V_{GS} = -10\text{ V}$ $V_{DS} = 40\text{ V}$ and $V_{GS} = -15\text{ V}$ (Typical 6.40 MeV/Nucleon at TAMU Cyclotron)
	2N7591	Surface LET = 61 MeV-cm ² /mg, range = 66 μm , Xe ion energy = 825 MeV In-situ bias conditions: $V_{DS} = 200\text{ V}$ and $V_{GS} = -10\text{ V}$, $V_{DS} = 190\text{ V}$ and $V_{GS} = -15\text{ V}$ (Typical 6.41 MeV/Nucleon at TAMU Cyclotron)
	2N7593	Surface LET = 61 MeV-cm ² /mg, range = 66 μm , Xe ion energy = 825 MeV In-situ bias conditions: $V_{DS} = 250\text{ V}$ and $V_{GS} = -10\text{ V}$, $V_{DS} = 50\text{ V}$ and $V_{GS} = -15\text{ V}$ (Typical 6.41 MeV/Nucleon at TAMU Cyclotron)
Post SEE electrical measurements	All devices in sample	I_{GSSF1} , I_{GSSR1} , and I_{DSS1} in accordance with table I, subgroup 2

See footnotes at end of table.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

TABLE IV. SEE characterization conditions for method 1080 of MIL-STD-750 – Continued. 1/

Inspection	Type	Irradiation conditions
Pre SEE electrical measurements SEE 3/	Applicable to manufacturer CAGE 69210 only – continued. 2/ Sample size of 3 devices. Applicable to devices with a date code of September 2009 and newer.	
	All devices in sample	I _{GSSF1} , I _{GSSR1} , and I _{DSS1} in accordance with table I, subgroup 2
		Fluence = $3 \times 10^5 \pm 20$ percent ions/cm ² Flux = 2×10^3 to 2×10^4 ions/cm ² /sec, temperature = $25 \pm 5^\circ\text{C}$
	2N7587	Surface LET = 90 MeV-cm ² /mg, range = 29 μm, Au ion energy = 375 MeV In-situ bias conditions: V _{DS} = 100 V and V _{GS} = -5 V, (Typical 1.88 MeV/Nucleon at TAMU Cyclotron)
	2N7589	Surface LET = 90 MeV-cm ² /mg, range = 80 μm, Au ion energy = 1472 MeV In-situ bias conditions: V _{DS} = 50 V and V _{GS} = -5 V, V _{DS} = 30 V and V _{GS} = -10 V (Typical 7.47 MeV/Nucleon at TAMU Cyclotron)
	2N7591	Surface LET = 90 MeV-cm ² /mg, range = 80 μm, Au ion energy = 1470 MeV In-situ bias conditions: V _{DS} = 150 V and V _{GS} = -4 V, V _{DS} = 110 V and V _{GS} = -5 V; (Typical 11.40 MeV/Nucleon at TAMU Cyclotron)
	2N7593	Surface LET = 90 MeV-cm ² /mg, range = 80 μm, Au ion energy = 1470 MeV In-situ bias conditions: V _{DS} = 75 V and V _{GS} = -5 V (Typical 6.40 MeV/Nucleon at TAMU Cyclotron)
Post SEE electrical measurements	All devices in sample	I _{GSSF1} , I _{GSSR1} , and I _{DSS1} in accordance with table I, subgroup 2

See footnotes at end of table.

MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

TABLE IV. SEE characterization conditions for method 1080 of [MIL-STD-750](#) – Continued. 1/

Inspection	Type	Irradiation conditions
Pre SEE electrical measurements SEE 3/	All devices in sample	Applicable to manufacturer CAGE 43611 only. Sample size of 3 devices. 2/ I_{GSSF1} , I_{GSSR1} , and I_{DSS1} in accordance with table I , subgroup 2 Fluence = $3 \times 10^5 \pm 20$ percent ions/cm ² Flux = 2×10^3 to 2×10^4 ions/cm ² /sec, temperature = $25 \pm 5^\circ\text{C}$ Surface LET = 43.9 MeV-cm ² /mg, range = 50 μm , Ag ion energy = 1330 MeV In-situ bias conditions: $V_{DS} = 100\text{ V}$ and $V_{GS} = -19\text{ V}$; $V_{DS} = 40\text{ V}$ and $V_{GS} = -20\text{ V}$ (Typical 3.80 MeV/Nucleon at Texas A & M Cyclotron)
	2N7587	
	2N7589	Surface LET = 38.6 MeV-cm ² /mg, range = 50.8 μm , Kr ion energy = 410 MeV In-situ bias conditions: $V_{DS} = 150\text{ V}$ and $V_{GS} = -20\text{ V}$, (Typical 4.89 MeV/Nucleon at TAMU Cyclotron)
	2N7591	Surface LET = 44 MeV-cm ² /mg, range = 117.3 μm , Ag ion energy = 1330 MeV In-situ bias conditions: $V_{DS} = 150\text{ V}$ and $V_{GS} = -10\text{ V}$, $V_{DS} = 130\text{ V}$ and $V_{GS} = -15\text{ V}$ (Typical 12.21 MeV/Nucleon at TAMU Cyclotron)
	2N7593	Surface LET = 44 MeV-cm ² /mg, range = 125 μm , Ag ion energy = 1350 MeV In-situ bias conditions: $V_{DS} = 250\text{ V}$ and $V_{GS} = -15\text{ V}$, $V_{DS} = 40\text{ V}$ and $V_{GS} = -20\text{ V}$ (Typical 10.05 MeV/Nucleon at TAMU Cyclotron)
	2N7587	Surface LET = 61 MeV-cm ² /mg, range = 66 μm , Xe ion energy = 825 MeV In-situ bias conditions: $V_{DS} = 100\text{ V}$ and $V_{GS} = -10\text{ V}$; $V_{DS} = 30\text{ V}$ and $V_{GS} = -15\text{ V}$ (Typical 2.70 MeV/Nucleon at TAMU Cyclotron)
	2N7589	Surface LET = 64 MeV-cm ² /mg, range = 69.9 μm , Xe ion energy = 942 MeV In-situ bias conditions: $V_{DS} = 150\text{ V}$ and $V_{GS} = -10\text{ V}$, $V_{DS} = 40\text{ V}$ and $V_{GS} = -15\text{ V}$ (Typical 7.31 MeV/Nucleon at TAMU Cyclotron)
	2N7591	Surface LET = 61 MeV-cm ² /mg, range = 83 μm , Xe ion energy = 1132 MeV In-situ bias conditions: $V_{DS} = 150\text{ V}$ and $V_{GS} = -10\text{ V}$, $V_{DS} = 100\text{ V}$ and $V_{GS} = -15\text{ V}$ (Typical 8.79 MeV/Nucleon at TAMU Cyclotron)
	2N7593	Surface LET = 61 MeV-cm ² /mg, range = 66 μm , Xe ion energy = 825 MeV In-situ bias conditions: $V_{DS} = 250\text{ V}$ and $V_{GS} = -10\text{ V}$, $V_{DS} = 50\text{ V}$ and $V_{GS} = -15\text{ V}$ (Typical 6.41 MeV/Nucleon at TAMU Cyclotron)

See footnotes at end of table.


MIL-PRF-19500/746D
w/AMENDMENT 5
DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

TABLE IV. SEE characterization conditions for method 1080 of [MIL-STD-750](#) – Continued. 1/


Inspection	Type	Irradiation conditions
Pre SEE electrical measurements	All devices in sample	Applicable to manufacturer CAGE 43611 only. Sample size of 3 devices. <u>2/</u> IGSSF1, IGSSR1, and IDSS1 in accordance with table I , subgroup 2
	2N7587	Surface LET = 90 MeV-cm ² /mg, range = 80 μm, Au ion energy = 1470 MeV In-situ bias conditions: V _{DS} = 100 V and V _{GS} = -4 V, (Typical 1.88 MeV/Nucleon at TAMU Cyclotron)
	2N7589	Surface LET = 90 MeV-cm ² /mg, range = 83.2 μm, Au ion energy = 1489 MeV In-situ bias conditions: V _{DS} = 50 V and V _{GS} = -5 V, V _{DS} = 30 V and V _{GS} = -10 V (Typical 7.56 MeV/Nucleon at TAMU Cyclotron)
	2N7591	Surface LET = 90 MeV-cm ² /mg, range = 82.5 μm, Au ion energy = 1476 MeV In-situ bias conditions: V _{DS} = 110 V and V _{GS} = -5 V (Typical 7.49 MeV/Nucleon at TAMU Cyclotron)
	2N7593	Surface LET = 90 MeV-cm ² /mg, range = 80 μm, Au ion energy = 1470 MeV In-situ bias conditions: V _{DS} = 250 V and V _{GS} = -5 V (Typical 6.40 MeV/Nucleon at TAMU Cyclotron)
Post SEE electrical measurements	All devices in sample	IGSSF1, IGSSR1, and IDSS1 in accordance with table I , subgroup 2

- 1/ Devices were tested in a TO-257 (T3) package for manufacturer 69210 or in a TO-204AA (TO-3) package for manufacturer 43611 in lieu of the TO-276AA (U3 or U3C) packages described by this specification sheet.
- 2/ Electrical measurements (IGSSF1, IGSSR1, and IDSS) were taken before and following SEE irradiation to determine acceptability for each bias condition. Other test conditions in accordance with [table I](#), subgroup 2 may be taken at the manufacturer's option.
- 3/ Manufacturer performed heavy ion SEE (SEB/SEGR) test at TAMU Radiation Effects Facility for the MOSFET technology devices in accordance with method 1080.0 of [MIL-STD-750](#). No single event burnout (SEB) and Single event gate rupture (SEGR) were observed to surface LET as stated above table IV and safe operating area (see figures [7](#), [8](#), [9](#), [10](#), [and 11](#), [and 12](#)). Limits are characterized at initial qualification and after any design or process changes which may affect the SEE (SEB/SEGR) characteristics. For more information on SEE (SEB/SEGR) test results, customers are requested to contact the qualified manufacturer.


2N7587



2N7589



2N7591



2N7593






FIGURE 7 8. Typical SEE safe operating area graphs (CAGE 69210).



NOTES:

1. LET for Ag is 43.9 $\pm$ 5 percent, 50 μ m $\pm$ 5 percent, 1330 MeV $\pm$ 5 percent.
2. LET for Xe is 61 $\pm$ 5 percent, 66 μ m $\pm$ 7.5 percent, 825 MeV $\pm$ 5 percent.
3. LET for Au is 90 $\pm$ 5 percent, 80 μ m $\pm$ 5 percent, 1470 MeV $\pm$ 5 percent.

FIGURE 8 9. Typical SEE safe operating area response (CAGE 43611).




NOTES:

1. LET for Kr is 38.6 $\pm$ 5 percent, 50.8 μ m $\pm$ 10 percent, 410 MeV $\pm$ 5 percent.
2. LET for Xe is 64 $\pm$ 5 percent, 69.9 μ m $\pm$ 7.5 percent, 942 MeV $\pm$ 5 percent.
3. LET for Au is 90 $\pm$ 5 percent, 83.2 μ m $\pm$ 5 percent, 1489 MeV $\pm$ 5 percent.

FIGURE 9 10. Typical SEE safe operating area response (CAGE 43611).

2N7591




NOTES:

1. LET for Ag is 43.9 ±5 percent, 117.3 μm ±10 percent, 1330 MeV ±5 percent.
2. LET for Xe is 61 ±5 percent, 83 μm ±7.5 percent, 1132 MeV ±5 percent.
3. LET for Au is 90 ±5 percent, 82.5 μm ±5 percent, 1476 MeV ±5 percent.

FIGURE 40 11. Typical SEE safe operating area response (CAGE 43611).

2N7593



NOTES:

1. LET for Ag is 44 ±5 percent, 125 μm ±10 percent, 1350 MeV ±5 percent.
2. LET for Xe is 61 ±5 percent, 66 μm ±7.5 percent, 825 MeV ±5 percent.
3. LET for Au is 90 ±5 percent, 80 μm ±5 percent, 1470 MeV ±5 percent.

MIL-PRF-19500/746D

w/AMENDMENT 5

DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

FIGURE ~~14~~ 12. Typical SEE safe operating area response (CAGE 43611).

MIL-PRF-19500/746D

w/AMENDMENT 5

DRAFT DATED: 22 April 2026 COMMENTS DUE BY 22 May 2026

6.8 Request for new types and configurations. Requests for new device types or configurations for inclusions in this specification sheet should be submitted to: DLA Land and Maritime Weapons Support, ATTN: VAC, Post Office Box 3990, Columbus, OH 43218-3990 or by electronic mail at Semiconductor@dla.mil.

6.9 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:

Army – CR
Navy – SH
Air Force – 85
NASA – NA
DLA – CC

Preparing activity:
DLA – CC

(Project 5961-2026-044)

Review activities:

Army – MI
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil>.