

INCH-POUND

MIL-S-19500/192B
6 October 1989
SUPERSEDING
MIL-S-19500/192A
19 April 1968

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, GERMANIUM, SWITCHING TYPE 1N276, JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for a germanium semiconductor diode. Three levels of product assurance are provided for each device type as specified in MIL-S-19500.

1.2 Physical dimensions. See figure 1 (DD-7).

1.3 Maximum ratings.

V_F	V_{RM}	I_0 1/	I_F	I_F (surge)	Operating ambient temperature	T_{STG}	Barometric pressure
V (pk)	V (pk)	mA dc	ma	1/120 second	°C	°C	mm Hg
100	70	40	150	$\frac{a}{0.5}$	-65 to +75	-65 to +100	8

1/ Derate I_0 linearly to 0.0 mA dc at +75°C.

1.4 Primary electrical characteristics. The diode shall have salient characteristics at ambient temperature of 25°C ±3°C, unless otherwise specified.

	V_F	I_R	i_r	I_R
	$I_F = 40$ mA dc	$V_R = 10$ V dc	$V_R = 100$ V(pk)	$V_R = 10$ V dc $T_A = +75^\circ\text{C}$
Min				
Max	1.0 V dc	20 μA	800 mA (pk)	100 μA dc

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Defense Electronics Supply Center, ATTN: DESC-ES, 1507 Wilmington Pike, Dayton, OH 45444-5276 by using the self-addressed Standardization Document Proposal (DD Form 1426) appearing at the end of this document or by letter.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

MILITARY

MIL-S-19500 - Semiconductor Devices, General Specification for.

STANDARD

MILITARY

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Detail specification. The individual item requirements shall be in accordance with MIL-S-19500, and as specified herein.


3.2 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-S-19500.

3.3 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-S-19500, and on figure 1.

3.3.1 Lead material and finish. Lead material shall be Dumet wire. Lead finish shall be tin plated or solder plated. Where a choice of lead material or finish is desired, it shall be specified in the contract or purchase order (see 6.2).

3.4 Marking. Marking shall be in accordance with MIL-S-19500. At the option of the manufacturer, the following marking may be omitted from the body of the diode.

- a. Manufacturer's identification
- b. Country of origin
- c. The "1N" portion of the type designation



Ltr	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A	.230	.300	5.84	7.62	
B	.085	.130	2.16	3.30	4
C	1.000	1.500	25.40	38.10	3
D	.018	.022	.46	.56	1, 2, and 3

NOTES:

1. The specified lead diameter applies in the zone between .050 (1.27 mm) and 1.000 (25.40 mm) from the diode body. Outside of this zone the lead diameter is not controlled.
2. Gold plated, tinned, or solder plated leads may be supplied providing units conform to subgroups 2 and 4 of group B inspection and subgroup 1 of group C inspection.
3. Both leads shall be within the specified dimension.
4. The minimum body diameter shall be maintained over .15 (0.38 mm) of body length.
5. Metric equivalents are given for general information only.

FIGURE 1. Semiconductor device, diode, type 1N276 (DO-7).

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-S-19500 and as specified herein.

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-S-19500.

4.3 Screening (JANTX and JANTXV levels only). Screening shall be in accordance with MIL-S-19500 (table II), and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Measurements	
Screen (see table II of MIL-S-19500)	JANTX and JANTXV levels
3	T_A = maximum rated storage temperature.
10	Test condition C, $T_A = 55^\circ\text{C}$, $T = 48$ hours minimum
11	I_{R1} and V_{F1}
12	See 4.3.1
13	Subgroup 2 of table I herein; ΔI_{R1} = 100% of initial reading or $5 \mu\text{A}$, whichever is greater. $\Delta V_{F1} = \pm 10\%$ of initial value.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows: All devices shall be operated at $25^\circ\text{C} \pm 3^\circ\text{C}$ under one of the following conditions:

Condition 1: See 4.5.3

$I_O = 40 \text{ mA dc}$

$V_R = 70 \text{ V pk}$

Condition 2: $I_F = 40 \text{ mA dc}$

4.4 Quality conformance inspection. Quality conformance inspection shall be in accordance with MIL-S-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-S-19500, and table I herein. (End point electrical measurements shall be in accordance with the applicable steps of table IV herein.)

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table IVb of MIL-S-19500 and table IIb herein. Electrical measurements (end points) and delta requirements shall be in accordance with the applicable steps of table IV herein.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table V of MIL-S-19500, and table III herein. Electrical measurements (end points) and delta requirements shall be in accordance with the applicable steps of table IV herein.

MIL-S-19500/192B

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
<u>Subgroup 1</u>						
Visual and mechanical examination	2071					
<u>Subgroup 2</u>						
Forward voltage	4011	$I_F = 10 \text{ mA dc (see 4.5.1)}$	V_{F1}		0.5	V dc
Forward voltage	4011	$I_F = 40 \text{ mA dc (see 4.5.1)}$	V_{F2}		1.0	V dc
Reverse current leakage	4016	$V_R = 10 \text{ V dc}$	I_{R1}		20	$\mu\text{A dc}$
Reverse current leakage	4016	$V_R = 50 \text{ V dc}$	I_{R2}		100	$\mu\text{A dc}$
Peak reverse voltage at peak reverse voltage	4016	$V_R = 100 \text{ V (pk)}$ AC method	i_r		800	$\mu\text{A (pk)}$
Reverse recovery time	4031	Test condition B, $V_R = 40 \text{ V dc}$, $I_F = 5 \text{ mA dc}$, $R_L = 2 \text{ k}\Omega$, $C = 10 \text{ pF}$, Recover to 100 $\text{k}\Omega$	t_{rr}		300	ns
Forward recovery voltage	4026	$I_F = 50 \text{ V dc}$	V_{fr}		3.0	V dc
Capacitance	4001	$V_R = 1.5 \text{ V dc}$ $V_R = 9 \text{ V dc}$	$C1$ $C2$		0.7 0.5	pF pF
<u>Subgroup 3</u>						
Reverse current leakage	4016	$T_A = 75^\circ\text{C}$, $V_R = 10 \text{ V dc}$, $V_R = 50 \text{ V dc}$, $t = 60 \text{ seconds}$	I_{R3} ΔI_R		100 10	$\mu\text{A dc}$ $\mu\text{A dc}$
<u>Subgroup 4</u>						
Not applicable						
<u>Subgroup 5</u>						
Not applicable						
<u>Subgroup 6</u>						
Surge current	4066	$I_0 = 40 \text{ mA dc}$, $i_f (\text{surge}) = 0.5 \text{ A}$, $t_p = 1/120 \text{ seconds}$, 10 surges at 1 per minute				
Electrical measurements		See table IV, steps 3 and 5.				

1/ For sampling plan, see MIL-S-19500.

TABLE IIb. Group B inspection for JAN, JANTX, and JANTXV.

Inspection <u>1/</u>	MIL-STD-750	
	Method	Conditions
<u>Subgroup 1</u>		
Solderability	2026	
Resistance to solvents	1022	
<u>Subgroup 2</u>		
Thermal shock (temperature cycling)	1051	Test condition A
Hermetic seal	1071	
a. Fine leak		Test condition H
b. Gross leak		Test condition E
Electrical measurements		See table IV, steps 1, 3, and 5.
<u>Subgroup 3</u>		
Steady-state operation life	1027	$f = 60 \text{ Hz}$, $I_0 = 40 \text{ mA dc}$, $V_r = 70 \text{ V (pk)}$ $t = 340 \text{ hours}$, $T_A = 25^\circ\text{C}$, see 4.5.3.
Electrical measurements		See table IV, steps 2, 3, and 4.
<u>Subgroup 4</u>		
Decap internal visual (design verification)	2075	
<u>Subgroup 5</u>		Qualification only.
Thermal resistance	4081	
<u>Subgroup 6</u>		
High temperature (nonoperating) life	1032	$T_A = 100^\circ\text{C}$
Electrical measurements		See table IV, steps 2, 3, and 4.

1/ For sampling plan, see MIL-S-19500.

TABLE III. Group C inspection (all quality levels).

Inspection 1/	MIL-STD-750	
	Method	Conditions
<u>Subgroup 1</u>		
Physical dimensions	2066	
<u>Subgroup 2</u>		
Thermal shock (glass strain)	1056	Test condition A
Terminal strength	2036	Test condition A, 4 pounds, $t = 15 \pm 3$ seconds
Hermetic seal	1071	
a. Fine leak		Test condition H
b. Gross leak		Test condition E
Moisture resistance	1021	
External visual	2071	
Electrical measurements		See table IV, steps 1, 3, and 5.
<u>Subgroup 3</u>		
Shock	2016	
Vibration, variable frequency	2056	
Constant acceleration	2006	
Electrical measurements		See table IV, steps 1, 3, and 5.
<u>Subgroup 4</u>		
Salt atmosphere (corrosion)	1041	
<u>Subgroup 5</u>		
Not applicable		
<u>Subgroup 6</u>		
Steady-state operation life	1026	$f = 60$ Hz, $T_A = 25^\circ\text{C}$, $I_0 = 40$ mA dc, V_r at 70 V pk, $t = 1,000$ hours, see 4.5.3.
Electrical measurements		See table IV, steps 2, 3, and 4.

1/ For sampling plan, see MIL-S-19500.

TABLE IV. Groups A, B, and C electrical measurements.

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Reverse current leakage	4016	$V_R = 10 \text{ V dc}$	I_{R1}		20	$\mu\text{A dc}$
2.	Reverse current leakage	4016	$V_R = 10 \text{ V dc}$	I_{R2}		100	$\mu\text{A dc}$
3.	Forward voltage	4011	$I_F = 40 \text{ mA dc}$	V_{F2}		1.0	V dc
4.	Reverse current leakage	4016	$V_R = 50 \text{ V dc}$	I_{R4}		150	$\mu\text{A dc}$
5.	Reverse current leakage	4016	$V_R = 50 \text{ V dc}$	I_{R3}		100	$\mu\text{A dc}$

MIL-S-19500/192B

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows:

4.5.1 Pulse measurements. Conditions for pulse measurements shall be as specified in section 4 of MIL-STD-750.

4.5.2 Time limit for end points. End points for qualification and quality conformance inspection shall be completed within 96 hours after completion of the last test in the subgroup.

4.5.3 Power burn-in criteria. This test shall be conducted with a half-sine wave of the specified peak voltage impressed across the diode in the reverse direction followed by a half-sine waveform of the specified average rectified current. The forward conduction angle of the rectified current shall be not greater than 180° nor less than 130°, and the power shall be equal to or greater than that of a half-sine wave.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-S-19500.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. The notes specified in MIL-S-19500 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents must specify the following:

- a. Title, number, and date of the specification.
- b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).
- c. Lead finish may be specified (see 3.3.1).

6.3 Substitution information. Devices covered by this specification are substitutable for the manufacturers' and users' Part or Identifying Number (PIN). This information in no way implies that manufacturers' PIN's are suitable as a substitute for the military PIN.

Military PIN	Manufacturers' CAGE code	Manufacturers' and users' PIN

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

CONCLUDING MATERIAL

Custodians:

Army - ER
Navy - EC
Air Force - 11

Review activities:

Army - AR
Air Force - 17, 85
Navy - SH
DLA - ES

User activities:

Army - MI, SM
Navy - AS, CG, MC, OS
Air Force - 19

Preparing activity:

Navy - EC

Agent:

DLA - ES

(Project 5961-1149)

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge (*DO NOT STAPLE*), and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES


OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 4966 Alexandria, VA

POSTAGE WILL BE PAID BY

Defense Electronics Supply Center
ATTN: DESC-ECT
Dayton, OH 45444-5280



STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER

2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION

4. TYPE OF ORGANIZATION (Mark one)

☐ VENDOR

☐ USER

☐ MANUFACTURER

☐ OTHER (Specify): _____

b. ADDRESS (Street, City, State, ZIP Code)

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER (Last, First, MI) – Optional

b. WORK TELEPHONE NUMBER (Include Area Code) – Optional

c. MAILING ADDRESS (Street, City, State, ZIP Code) – Optional

8. DATE OF SUBMISSION (YYMMDD)