

INCH-POUND

MS25269M
24 August 2020
SUPERSEDING
MS25269L
27 November 2003

DETAIL SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 5 AMPERES, 6 PDT,
TYPE I, HERMETICALLY SEALED

INACTIVE FOR NEW DESIGN AFTER 15 OCTOBER
1999. NO SUPERSEDING SPECIFICATION.

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall
consist of this specification and the latest issue of [MIL-PRF-6106](#).





FIGURE 1. Dimensions and configuration.



MS25269M



Inches	mm	Inches	mm
.001	0.03	.450	11.43
.003	0.08	.562	14.27
.005	0.13	.593	15.06
.040	1.02	.900	22.86
.062	1.57	1.125	28.58
.138	3.51	1.187	30.15
.152	3.86	1.531	38.89
.235	5.97	1.812	46.02
.375	9.53		

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± 0.010 (0.25 mm).
4. In the event of a conflict between the text of this standard and the references cited herein, the text of this standard shall take precedence.
5. Referenced Government documents of the issue listed in Assist Online (<https://assist.dla.mil/>) or Assist Quick Search (<https://quicksearch.dla.mil/>) specified in the solicitation form a part of this specification to the extent specified herein.
6. Terminal numbers shall not appear on the relay header. There shall be affixed to the relay a legible circuit diagram that identifies each terminal location specified.

FIGURE 1. Dimensions and configuration - Continued.

REQUIREMENTS:

Dimensions and configuration: See [figure 1](#).

Part or Identifying Numbers (PIN's) and general characteristics: See [table I](#).

Contact data:

Load ratings: See [table II](#).

Maximum contact drop, initial: 0.150 V.

After life test: 0.175 V.

Overload current: 20 amperes.

Rupture current: 25 amperes.

Coil data: See [table III](#).

Duty rating: Continuous.

RFI specification: [MIL-STD-461](#) (applicable to coil of ac operated relays).

Electrical data:

Minimum insulation resistance:

Initial: 100 megohms.

After life or environmental test: 50 megohms.

Dielectric strength (sea level)

	Initial	After life tests
Coil to case	1,000 V rms	1,000 V rms
Aux contacts	N/A	N/A
All other points	1,000 V rms	1,000 V rms

Dielectric strength (altitude)

	80,000 ft
Coil to case	250 V rms
Aux contacts	N/A
All other points	250 V rms

MS25269M

Environmental characteristics:

Temperature range: -70°C to +120°C.

Maximum altitude rating: 80,000 feet.

Shock, g-level: 50 g's.

Duration: 6-9 ms.

Maximum duration contact opening: 10 μ s.

Vibration - sinusoidal:

G-level: 10 g's.

Frequency range: 5 - 1,500 Hz.

Vibration - random:

Applicable specification: Not applicable.

Power spectral density: Not applicable.

RMS G-minimum: Not applicable.

Frequency range: Not applicable.

Curve: Not applicable.

High shock: Not applicable.

Acceleration: 15 g's.

Qualification by similarity: See [MIL-PRF-6106](#).

Group B and C inspections may be suspended at the discretion of the qualifying activity.

PIN: MS25269- (plus applicable dash number from [table I](#)).

TABLE I. PIN's and general characteristics.

PIN MS25269-	Type	Coil	Terminal type	Mounting type	Maximum weight (pounds)
D1	I	dc	Solder hook	Stud	0.35
A1	I	ac	Solder hook	Stud	0.35

MS25269M

TABLE II. Rated contact load (amperes per pole) case grounded.

Type of load	Life operating cycles x 10 ³	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase <u>1/</u>			
		Main		Aux		Main		Aux		Main		Aux	
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz
Resistive	100 <u>3/</u>	5	5			5	4						
Inductive	100 <u>3/</u>												
Inductive	20 <u>3/</u>	3	3			3	2						
Motor	100 <u>3/</u>	1.5	1.5			1.5	1						
Lamp	100 <u>3/</u>	0.8	0.8			0.8	0.6						
Transfer load <u>2/</u>													
Mechanical life (reduced current)	400 <u>3/</u>	1.25	1.25			1.25	1						
Mixed loads		Applicable in accordance with <u>MIL-PRF-6106</u>											

1/ Absence of value indicates the relay is not rated for 3 phase application.

2/ Transfer load indicates the relay is suitable for transfer between unsynchronized ac power supplies at the rating indicated.

3/ MS25269-A1 is rated for 50,000 cycles, except that inductive is 10,000 cycles and mechanical life is 200,000 cycles.

TABLE III. Operating characteristics.

PIN MS25269-	Coil data										Time - (milliseconds maximum)						
	Coil	Rated			Max		Max pick-up voltage			Hold voltage 2/	Drop- out voltage 2/	Operate 3/	Release 4/	Bounce			
		Volts 1/	Freq. (Hz)	Res (Ω)	Volts	Amperes	Normal 2/	High temp test	Cont current test					Main		Aux	
														NO	NC	NO	NC
D1	X1,X2	28	dc		29	0.18	18	19.8	22.5	7.0	1.5	20	20	2	2		
A1	X1,X2	115	400 5/		122	0.04	90	95	103	30	5.0	25	50	2	2		

1/ CAUTION: Use of any coil voltage less than rated coil voltage will compromise the operation of the relay.

2/ Over the temperature range.

3/ With rated coil voltage.

4/ From rated coil voltage.

5/ MS25269-A1 may be used on 60 Hz if ambient temperature is limited to 85°C maximum and current is limited to 0.044 ampere maximum.

MS25269M

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. In addition to [MIL-PRF-6106](#), this document references the following:
[MIL-STD-461](#)

Custodians:
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

Project 5945-2020-041

Review activity:
Navy - EC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil/>.