

QUALIFICATIONS VALIDATED
SEMIANNUALLY

QPL-26-120
5 February 1987
~~SUPERSEDING~~
QPL-26-119
14 November 1986

QUALIFIED PRODUCTS LIST
OF
PRODUCTS QUALIFIED UNDER MILITARY SPECIFICATION
MIL-R-26
RESISTORS, FIXED, WIRE-WOUND (POWER TYPE)
GENERAL SPECIFICATION FOR

FSC 5905

This list has been prepared for use by or for the Government in the acquisition of products covered by Specification MIL-R-26. Listing of a product is not intended to and does not connote endorsement of the product by the Department of Defense. All products listed herein have been qualified under the requirements for the product as specified in the latest effective issue of the applicable specification. This list is subject to change without notice. Revision or amendment of this list will be issued as necessary. The listing of a product does not release the supplier from compliance with the specification requirements.

THE ACTIVITY RESPONSIBLE FOR THIS QUALIFIED PRODUCTS LIST IS THE U.S. ARMY LABORATORY COMMAND (LABCOM). The Defense Electronics Supply Center (DESC-EQ) has been designated as agent for the establishment and maintenance of this QPL.

NOTE: When the detail specification requires qualification and there are no products listed or approved for listing on the QPL or when suppliers of those products on the QPL are nonresponsive to an IFB, the qualification requirement of paragraph 3.2 of MIL-R-26 may be waived for procurement of Resistors, Fixed, Wire-Wound (Power Type), only by the Preparing Activity. When qualification is waived, procuring activities shall invoke first article inspection. First article inspection shall consist of performing all qualification tests. The sample size and allowable defects shall be in accordance with the detail specification and MIL-R-26 qualification sampling and acceptance criteria. A copy of the test data shall be forwarded to the qualifying activity.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW20 thru RW24 Char. V, min. wire size 0.00175".		26-269-75	/2	Dale Electronics, Inc. (2)
RW20: 0.1 ohm thru 8,200 ohms.	HL-24-09Z HLT-24-09Z			
RW21: 0.1 ohm thru 16,000 ohms.	HL-35-09Z HLT-35-09Z			
RW22: 0.1 ohm thru 36,000 ohms	HL-55-09Z HLT-55-09Z			
RW23: 0.1 ohm thru 51,000 ohms.	HL-70-09Z HLT-70-09Z			
RW24: 0.1 ohm thru 75,000 ohms.	HL-95-09Z HLT-95-09Z			

AMSC N/A

1 of 14
QPL-26-120

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW20 thru RW24 Char. V, min. wire size 0.00175".		26-483-71	/2	Memcor-Truohm, Inc.
RW20: 0.1 ohm thru 3,200 ohms.	OR20			
RW21: 0.1 ohm thru 6,600 ohms.	OR21			
RW22: 0.1 ohm thru 13,000 ohms.	OR22			
RW23: 0.1 ohm thru 19,000 ohms.	OR23			
RW24: 0.1 ohm thru 25,000 ohms.	OR24			
RW20 thru RW24 Char. V, min. wire size 0.00175".		26-823-66	/2	Ohmite Manufacturing Co.
RW20: 0.1 ohm thru 8,200 ohms.	RW20			
RW21: 0.1 ohm thru 16,000 ohms.	RW21			
RW22: 0.1 ohm thru 36,000 ohms.	RW22			
RW23: 0.1 ohm thru 51,000 ohms.	RW23			
RW24: 0.1 ohm thru 75,000 ohms.	RW24			
RW20 thru RW24 Char. V, min. wire size 0.00175".		26-687-68	/2	Ward Leonard Electric Co.
RW20: 0.1 ohm thru 8,200 ohms.	VWL-RW20			
RW21: 0.1 ohm thru 16,000 ohms.	VWL-RW21			
RW22: 0.1 ohm thru 36,000 ohms.	VWL-RW22			
RW23: 0.1 ohm thru 51,000 ohms.	VWL-RW23			
RW24: 0.1 ohm thru 75,000 ohms.	VWL-RW24			
RW29 thru RW33, RW35 thru RW38, and RW47 Char. F, min. wire size 0.00175".		26-270-75	/3	Dale Electronics, Inc. (2)
RW29: 0.1 ohm thru 5,600 ohms.	HL-11-02Z HLT-11-02Z			
RW30: 0.1 ohm thru 2,700 ohms.	HL-10-02Z HLT-10-02Z			
RW31: 0.1 ohm thru 6,800 ohms.	HL-15-02Z HLT-15-02Z			
RW32: 0.1 ohm thru 10,000 ohms.	HL-20-02Z HLT-20-02Z			
RW33: 0.1 ohm thru 18,000 ohms.	HL-26-02Z HLT-26-02Z			
RW35: 0.1 ohm thru 43,000 ohms.	HL-60-03Z HLT-60-03Z			
RW36: 0.1 ohm thru 56,000 ohms.	HL-80-04Z HLT-80-04Z			
RW37: 0.1 ohm thru 91,000 ohms.	HL-120-04Z HLT-120-04Z			
RW38: 0.1 ohm thru 0.15 megohm.	HL-160-04Z HLT-160-04Z			
RW47: 0.1 ohm thru 0.16 megohm.	HL-225-04Z HLT-225-04Z			

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW29 thru RW39, and RW47 Char. V, min. wire size 0.00175".		26-792A-66	/3	Memcor-Truohm, Inc.
RW29: 0.1 ohm thru 1,500 ohms.	FR-RW29			
RW30: 0.1 ohm thru 750 ohms.	FR-RW30			
RW31: 0.1 ohm thru 1,800 ohms.	FR-RW31			
RW32: 0.1 ohm thru 2,400 ohms.	FR-RW32			
RW33: 0.1 ohm thru 4,700 ohms.	FR-RW33			
RW34: 0.1 ohm thru 8,200 ohms.	FR-RW34			
RW35: 0.1 ohm thru 11,000 ohms.	FR-RW35			
RW36: 0.1 ohm thru 15,000 ohms.	FR-RW36			
RW37: 0.1 ohm thru 24,000 ohms.	FR-RW37			
RW38: 0.1 ohm thru 39,000 ohms.	FR-RW38			
RW39: 0.1 ohm thru 51,000 ohms.	FR-RW39			
RW47: 0.1 ohm thru 43,000 ohms.	FR-RW47			
RW29 thru RW39, and RW47 Char. V, min. wire size 0.00175".		26-824-66	/3	Ohmite Manufacturing Co.
RW29: 0.1 ohm thru 2,700 ohms.	RW29			
RW30: 0.1 ohm thru 2,700 ohms.	RW30			
RW31: 0.1 ohm thru 6,800 ohms.	RW31			
RW32: 0.1 ohm thru 10,000 ohms.	RW32			
RW33: 0.1 ohm thru 18,000 ohms.	RW33			
RW34: 0.1 ohm thru 30,000 ohms.	RW34			
RW35: 0.1 ohm thru 43,000 ohms.	RW35			
RW36: 0.1 ohm thru 56,000 ohms.	RW36			
RW37: 0.1 ohm thru 91,000 ohms.	RW37			
RW38: 0.1 ohm thru 0.15 megohm.	RW38			
RW39: 0.1 ohm thru 0.20 megohm.	RW39			
RW47: 0.1 ohm thru 0.18 megohm.	RW47			

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW29, RW31, RW33, RW35, RW37, RW38, and RW47 Char. N, min. wire size 0.00175".		26-45-77	/3	Ohmite Manufacturing Co.
RW29: 0.1 ohm thru 2,700 ohms.	RW29N			
RW31: 0.1 ohm thru 3,300 ohms.	RW31N			
RW33: 0.1 ohm thru 8,100 ohms.	RW33N			
RW35: 0.1 ohm thru 20,000 ohms.	RW35N			
RW37: 0.1 ohm thru 43,000 ohms.	RW37N			
RW38: 0.1 ohm thru 75,000 ohms.	RW38N			
RW47: 0.1 ohm thru 81,000 ohms.	RW47N			
RW29 thru RW38, and RW47 Char. V, min. wire size 0.00175".		26-688-68	/3	Ward Leonard Electric Co.
RW29: 0.1 ohm thru 5,600 ohms.	VWL-RW29			
RW30: 0.1 ohm thru 2,700 ohms.	VWL-RW30			
RW31: 0.1 ohm thru 6,800 ohms.	VWL-RW31			
RW32: 0.1 ohm thru 10,000 ohms.	VWL-RW32			
RW33: 0.1 ohm thru 18,000 ohms.	VWL-RW33			
RW34: 0.1 ohm thru 30,000 ohms.	VWL-RW34			
RW35: 0.1 ohm thru 43,000 ohms.	VWL-RW35			
RW36: 0.1 ohm thru 56,000 ohms.	VWL-RW36			
RW37: 0.1 ohm thru 91,000 ohms.	VWL-RW37			
RW38: 0.1 ohm thru 0.15 megohm.	VWL-RW38			
RW47: 0.1 ohm thru 0.18 megohm.	VWL-RW47			
RW55 and RW56 Char. V, min. wire size 0.00175" single-layer winding.		26-657-66	/4	CAL-R, Inc.
RW55: 0.1 ohm thru 5,100 ohms.	SA-95			
RW56: 0.1 ohm thru 9,100 ohms.	SA-125			
RW55 and RW56 Char. V, min. wire size 0.00175".	HLR	26-793-66	/4	Memcor-Truohm, Inc.
RW55: 0.1 ohm thru 5,100 ohms.				
RW56: 0.1 ohm thru 9,100 ohms.				

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW55 and RW56 Char. V, min. wire size 0.00175". RW55: 0.1 ohm thru 5,000 ohms. RW56: 0.1 ohm thru 9,100 ohms.	1900S 1950S	26-606-66	/4	Nytronics Components Group, Inc.
RW55 and RW56 Char. V, min. wire size 0.00175". RW55: 0.1 ohm thru 5,100 ohms. RW56: 0.1 ohm thru 9,100 ohms.	56AC	26-73-67	/4	Pacific Resistor Co.
RW55 and RW56 Char. V, min. wire size 0.00175". RW55: 0.1 ohm thru 5,100 ohms. RW56: 0.1 ohm thru 9,100 ohms.	T-10A	26-971-66	/4	RCL Electronics, Inc.
RW55 Char. V, min. wire size 0.00175", res. tol. 0.1 ohm thru 3,400 ohms.	T-7A-55	26-381-85	/4	Shallcross, Inc. (2)
RW55 and RW56 Char. V, min. wire size 0.00175". RW55: 0.1 ohm thru 5,100 ohms. RW56: 0.1 ohm thru 9,100 ohms.	VWL-RW55 VWL-RW56	26-689-66	/4	Ward Leonard Electric Co.
RW67 thru RW69 Char. V, min. wire size 0.001". RW67: 0.1 ohm thru 8,200 ohms. RW68: 0.1 ohm thru 20,000 ohms. RW69: 0.1 ohm thru 2,000 ohms.	SA-55 SA-100 SA-30	26-658-66	/4	CAL-R, Inc.
RW67 thru RW69 Char. V, min. wire size 0.001". RW67: 0.1 ohm thru 8,200 ohms. RW68: 0.1 ohm thru 20,000 ohms. RW69: 0.1 ohm thru 2,000 ohms.	CW-5-5 CW-5-125 CW-10-4 CW-10-125 CW-2C-1 CW-2C-125	26-719-66	/4	Dale Electronics, Inc. (1)

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW67 thru RW69 Char. V, min. wire size 0.001".		26-86-81	/4	Dale Electronics, Inc. (5)
RW67: 0.1 ohm thru 8,200 ohms.	CW-5-5 CW-5-125			
RW68: 0.1 ohm thru 20,000 ohms.	CW-10-4 CW-10-125			
RW69: 0.1 ohm thru 2,000 ohms.	CW-20-1 CW-20-125			
RW67 thru RW69 Char. V, min. wire size 0.00175".		26-1115-67	/4	Memcor-Truohm, Inc.
RW67: 0.1 ohm thru 3,600 ohms.	RW67			
RW68: 0.1 ohm thru 8,200 ohms.	RW68			
RW69: 0.1 ohm thru 910 ohms.	RW69			
RW67 thru RW69 Char. V, min. wire size 0.001".		26-607-66	/4	Nytronics Components Group, Inc.
RW67: 0.1 ohm thru 8,200 ohms.	1550S			
RW68: 0.1 ohm thru 20,000 ohms.	1700S			
RW69: 0.1 ohm thru 2,000 ohms.	1200S			
RW67 thru RW69 Char. V, min. wire size 0.001".		26-293-76 26-1047-84	/4	Ohmite Manufacturing Co.
RW67: 0.1 ohm thru 8,200 ohms.	RW67(226)			
RW68: 0.1 ohm thru 20,000 ohms.	RW68(220)			
RW69: 0.1 ohm thru 2,000 ohms.	RW69(223)			
RW67 thru RW69 Char. V, min. wire size 0.001".		26-825-66 26-795-68	/4	Ohmite Manufacturing Co.
RW67: 0.1 ohm thru 8,200 ohms.	85J			
RW68: 0.1 ohm thru 20,000 ohms.	80J			
RW69: 0.1 ohm thru 2,000 ohms.	83J			
RW67 thru RW69 Char. V, min. wire size 0.001".		26-563-67	/4	Pacific Resistor Co.
RW67: 0.1 ohm thru 8,200 ohms.	5A			
RW68: 0.1 ohm thru 20,000 ohms.	10A			
RW69: 0.1 ohm thru 2,000 ohms.	MN1A			

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW67 thru RW69 Char. V, min. wire size 0.001". RW67: 0.1 ohm thru 8,200 ohms. RW68: 0.1 ohm thru 20,000 ohms. RW69: 0.1 ohm thru 2,000 ohms.	T-6-67 T-10-68 T-2A-69	26-972-66	/4	RCL Electronics, Inc.
RW67 thru RW69 Char. V, min. wire size 0.001". RW67: 0.1 ohm thru 8,200 ohms. RW68: 0.1 ohm thru 20,000 ohms. RW69: 0.1 ohm thru 2,000 ohms.	LA419 LA433 LA417	26-603-69	/4	Shallcross, Inc. (1)
RW69 Char. V, min. wire size 0.001", res. tol. 0.1 ohm thru 2,000 ohms.	T-2A-69	26-382-85	/4	Shallcross, Inc. (2)
RW67 thru RW69 Char. V, min. wire wire size 0.001". RW67: 0.1 ohm thru 8,200 ohms. RW68: 0.1 ohm thru 20,000 ohms. RW69: 0.1 ohm thru 2,000 ohms.	EL5A EL10A EL2C	26-1302-68	/4	Tel-Labs, Inc.
RW67 thru RW69 Char. V, min. wire size 0.001". RW67: 0.1 ohm thru 8,200 ohms. RW68: 0.1 ohm thru 20,000 ohms. RW69: 0.1 ohm thru 2,000 ohms.	CS-7 CS-11 CS-3	26-668-81	/4	Ultronix, Inc.
RW67 thru RW69 Char. V, min. wire size 0.001". RW67: 0.1 ohm thru 8,200 ohms. RW68: 0.1 ohm thru 20,000 ohms. RW69: 0.1 ohm thru 2,000 ohms.	VWL RW67 VWL RW68 VWL RW69	26-690-68	/4	Ward Leonard Electric Co.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW67 thru RW69 Char. V, min. wire size 0.0001".		26-691-68	/4	Ward Leonard Electric Co.
RW67: 0.1 ohm thru 8,200 ohms.	SWL RW67			
RW68: 0.1 ohm thru 20,000 ohms.	SWL RW68			
RW69: 0.1 ohm thru 2,000 ohms.	SWL RW69			
RW70 and RW79 Char. U, min. wire size 0.0008", res. tol. B, D, and F.		26-660-66	/5	CAL-R, Inc.
RW70: 0.1 ohm thru 3,160 ohms.	SA15			
RW79: 0.1 ohm thru 10,500 ohms.	SA31			
RW70 and RW79 Char. U, min. wire size 0.0008", res. tol. B, D, and F.		26-208-66	/5	Dale Electronics, Inc. (1)
RW70: 0.1 ohm thru 2,740 ohms.	RS-1A RS-1A-125			
RW79: 0.1 ohm thru 6,490 ohms.	RS-2B RS-2B-125			
RW70 and RW79 Char. U, min. wire size 0.001", res. tol. F.		26-85-81	/5	Dale Electronics, Inc. (5)
RW70: 0.1 ohm thru 1,210 ohms.	RS-1A RS-1A-125			
RW79: 0.1 ohm thru 2,430 ohms.	RS-2B RS-2B-125			
RW70 and RW79 Char. U, min. wire size 0.0008", res. tol. B, D, and F.		26-609-66	/5	Nytronics Components Group, Inc.
RW70: 0.1 ohm thru 3,160 ohms.	1000S			
RW79: 0.1 ohm thru 10,500 ohms.	1240S			
RW70 and RW79 Char. U, min. wire size 0.0008", res. tol. B, D, and F.		26-632-67	/5	Ohmite Manufacturing Co.
RW70: 0.1 ohm thru 3,160 ohms.	81F, 81D, 81B			
RW79: 0.1 ohm thru 10,500 ohms.	83F, 83D, 83B			

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW/U and RW/9 Char. U, min. wire size 0.0008", res. tol. F. RW70: 0.1 ohm thru 3,160 ohms RW79: 0.1 ohm thru 6,040 ohms.	15A N1A	26-75-67	/5	Pacific Resistor Co.
RW70 and RW79 Char. U, min. wire size 0.0008", res. tols. B, U, and F. RW70: 0.1 ohm thru 3,160 ohms. RW79: 0.1 ohm thru 10,500 ohms.	T-1A-70 T-2B-79	26-1025-69	/5	RCL Electronics, Inc.
RW70 and RW79 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW70: 0.1 ohm thru 3,160 ohms. RW79: 0.1 ohm thru 10,500 ohms.	LA449 LA461	26-972-71	/5	Shallcross, Inc. (1)
RW70 and RW79 Char. U, min. wire size 0.0008", res. tol. F. RW70: 0.1 ohm thru 3,160 ohms. RW79: 0.1 ohm thru 6,700 ohms.	T-2B-79	26-384-85	/5	Shallcross, Inc. (2)
RW70 and RW79 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW70: 0.1 ohm thru 3,160 ohms. RW79: 0.1 ohm thru 10,500 ohms.	EL1A EL21	26-478-69	/5	Tel-Labs, Inc.
RW70 and RW79 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW70: 0.1 ohm thru 2,740 ohms. RW79: 0.1 ohm thru 6,040 ohms.	TS1A TS2B	26-1366-77	/5	Tepro of Florida, Inc.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW70 and RW79 Char. U, min. wire size 0.0008", res. tol. B, D, and F. RW70: 0.1 ohm thru 3,160 ohms. RW79: 0.1 ohm thru 10, 500 ohms.	MS-2 CS-4	26-635-75 26-669-81	/5	Ultronix, Inc.
RW70 and RW79 Char. U, min. wire size 0.0008", res. tol. F. RW70: 0.1 ohm thru 3,160 ohms. RW79: 0.1 ohm thru 10,500 ohms.	SWL RW70 SWL RW79	26-1018-69	/5	Ward Leonard Electric Company
RW74 and RW78 Char. U, min. wire size 0.0008", res. tol. B, D, and F. RW74: 0.1 ohm thru 38,300 ohms. RW78: 0.1 ohm thru 90,900 ohms.	SA50 SA100	26-659-66	/5	CAL-R, Inc.
RW74 and RW78 Char. U, min. wire size 0.0008", res. tol. B, D, and F. RW74: 0.1 ohm thru 24,300 ohms. RW78: 0.1 ohm thru 71,500 ohms.	RS-5-69 RS-5-125 RS-10-38 RS-10-125	26-207-66	/5	Dale Electronics, Inc. (1)
RW74 and RW78 Char. U, min. wire size 0.001", res. tol. F. RW74: 0.1 ohm thru 9,090 ohms. RW78: 0.1 ohm thru 26,700 ohms.	RS-5-69 RS-5-125 RS-10-38 RS-10-125	26-416-81	/5	Dale Electronics, Inc. (5)
RW74 and RW78 Char. U, min. wire size 0.0008", res. tol. F. RW74: 10 ohms thru 38,300 ohms. RW78: 10 ohms thru 51,100 ohms.	SL-0005 SL-0010	26-73-85	/5	Memcor-Iruehm, Inc.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW74 and RW78 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW74: 0.1 ohm thru 38,300 ohms. RW78: 0.1 ohm thru 90,900 ohms.	1500S 1700S	26-608-66	/5	Nytronics Components Group, Inc.
RW74 and RW78 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW74: 0.1 ohm thru 38,300 ohms. RW78: 0.1 ohm thru 90,900 ohms.	85F, 85D, 85B 80F, 80D, 80B	26-631-67	/5	Ohmite Manufacturing Co.
RW74 and RW78 Char. U, min. wire size 0.001", res. tol. F. RW74: 0.1 ohm thru 12,100 ohms. RW78: 0.1 ohm thru 40,200 ohms.	5AV 10AV	26-74-67	/5	Pacific Resistor Co.
RW74 and RW78 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW74: 0.1 ohm thru 38,000 ohms. RW78: 0.1 ohm thru 90,900 ohms.	T-5-74 T-10-78	26-1026-69	/5	RCL Electronics, Inc.
RW74 and RW78 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW74: 0.1 ohm thru 38,300 ohms. RW78: 0.1 ohm thru 90,900 ohms.	LA446 LA433	26-971-71	/5	Shallcross, Inc. (1)
RW74 Char. U, min. wire size 0.0008", res. tol. F, 0.1 ohm thru 17,000 ohms.	T-5-74	26-383-85	/5	Shallcross, Inc. (2)

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW74 and RW78 Char. U, min. wire size 0.001", res. tol. F.			/5	Ultronix, Inc.
RW74: 0.1 ohm thru 12,100 ohms.	CS-6	39007-313-78		
RW78: 0.1 ohm thru 39,200 ohms.	CS-10	39007-314-78		
RW74 and RW78 Char. U, min. wire size 0.0008", res. tol. F.		26-1017-69	/5	Ward Leonard Electric. Company
RW74: 0.1 ohm thru 38,300 ohms.	SWL RW74			
RW78: 0.1 ohm thru 90,900 ohms.	SWL RW78			
RW79 Char. U, min. wire size 0.0008" res. tol. F, 0.1 ohm thru 6,490 ohms.	RS-2B RS-2B-125	26-1060-76	/5	Dale Electronics, Inc. (1)
RW79 Char. U, min. wire size 0.00175", res. tol. F, 0.1 ohm thru 49.9 ohms.	RS-2B RS-2B-125	26-620-80	/5	Dale Electronics, Inc. (5)
RW79 Char. U, min. wire size 0.0008", res. tol. F, 10 ohms thru 6,040 ohms.	SL-0003	26-73-85	/5	Memcor-Truohm, Inc.
RW80 and RW81 Char. U, min. wire size 0.0008". res. tols. B, D, and F.		26-661-66	/6	CAL-R, Inc.
RW80: 0.1 ohm thru 3,160 ohms.	SA15			
RW81: 0.1 ohm thru 1,000 ohms.	SA02			
RW80 and RW81 Char. U, min. wire size 0.0008", res. tols. B, D, and F.		26-209-66	/6	Dale Electronics, Inc. (1)
RW80: 0.1 ohm thru 2,740 ohms.	G-3 G-3-80 G-3-125			
RW81: 0.1 ohm thru 1,000 ohms.	G-1 G-1-80 G-1-125			

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW80 and RW81 Char. U, min. wire size 0.0008", res. tol. B, D, and F. RW80: 0.2 ohm thru 3,160 ohms. RW81: 0.1 ohm thru 1,000 ohms.	1000SB 250SB	26-610-66	/6	Nytronics Components Group, Inc.
RW80 and RW81 Char. U, min. wire size 0.0008", res. tol. F. RW80: 0.1 ohm thru 3,160 ohms. RW81: 0.1 ohm thru 649 ohms.	B3 B1	26-76-67	/6	Pacific Resistor Co.
RW80 and RW81 Char. U, min. wire size 0.0008", res. tol. B, D, and F. RW80: 0.1 ohm thru 3,160 ohms. RW81: 0.1 ohm thru 1,000 ohms.	T1-80 B-3 T1/2A-81 B-1	26-1027-69	/6	RCL Electronics, Inc.
RW80 and RW81 Char. U, min. wire size 0.0008", res. tol. B, D, and F. RW80: 0.1 ohm thru 3,160 ohms. RW81: 0.1 ohm thru 1,000 ohms.	LA49 LA68 LA268	26-475-72	/6	Shallcross, Inc. (1)
RW80 and RW81 Char. U, min. wire size 0.0008", res. tol. F. RW80: 0.1 ohm thru 1,800 ohms. RW81: 0.1 ohm thru 1,000 ohms.	T-1-80	26-385-85	/6	Shallcross, Inc. (2)
RW80 and RW81 Char. U, min. wire size 0.0008", res. tol. F. RW80: 0.1 ohm thru 2,670 ohms. RW81: 0.1 ohm thru 1,000 ohms.	MS-2 MS-1	39007-777-71 39007-778-71	/6	Ultronix, Inc.

MANUFACTURER'S NAME, ADDRESS AND PLANT	CAGE CODE	MANUFACTURER'S NAME, ADDRESS AND PLANT	CAGE CODE
CAL-R, Inc. 1601 Olympic Boulevard Santa Monica, CA 90404 Plant: Same Address	14193	TEL-Labs, Inc. 154 Harvey Road Londonderry, NH 03053 Plant: Same Address	94322
Dale Electronics, Inc. P.O. Box 609 Columbus, NE 68601 Plants: 1. Industrial Site (Plant 2) East Highway 30 Columbus, NE 2. 2922 Division Avenue York, NE 3. Dale Electronics, GMBH 895 Kaufberuren-Neugablong Falkenstrosse, 17 West Germany 5. Electronics Dale De Mexico Bartolome De Los Cosas Jesus Futa. Juarez, Mexico	91637	Tepro of Florida, Inc. 2608 Enterprise Road Dunedin, FL 33528 Plant: Same Address Ultronix, Inc. P.O. Box 1090 461 North 22nd Street Grand Junction, CO 81501 Plant: Same Address Ward Leonard Electric Company 31 South Street Mount Vernon, NY 10550 Plant: Same Address	15915 05347 63743
Memcor-Truohm, Inc. 1320 Flaxmill Road Huntington, IN 46750 Plant: Same Address	83777		
Nytronics Components Group, Inc. Orange Street Darlington, SC 29532 Plant: Same Address	00213		
Ohmite Manufacturing Company 3601 Howard Street Skokie, IL 60076 Plant Same Address	44655		
Pacific Resistor Company 18300 Oxnard Street Tarzana, CA 91356 Plant: Same Address	06416		
RCL Electronics, Inc. 196 McGregor Street Manchester, NH 03102 Plant: Same Address	01686		
Shallcross, Inc. U.S. 70 East Smithfield, NC 27577 Plant: 1. Same Address 2. RCL/Shallcross RVE Hyppolite Port Au Prince Haiti, W.I.	54294		