QUALIFICATIONS VALIDATED
SEMIANNUALLY

QPL-26-147
20 November 1997
SUPERSEDING
QPL-26-146
8 October 1997

QUALIFIED PRODUCTS LIST

OF

PRODUCTS QUALIFIED UNDER MILITARY SPECIFICATION

MIL-R-26

RESISTOR, FIXED, WIRE-WOUND (POWER TYPE)

GENERAL SPECIFICATION FOR

This list has been prepared for use by or for the Government in the acquisition of products covered by Specification MIL-R-26. Listing of a product is not intended to and does not connote endorsement of the product by the Department of Defense. All products listed herein have been qualified under the requirements for the product as specified in the latest effective issue of the applicable specification. This list is subject to change without notice; revision or amendment of this list will be issued as necessary. The listing of a product does not release the supplier from compliance with the specification requirements.

THE ACTIVITY RESPONSIBLE FOR THIS QPL IS THE DEFENSE SUPPLY CENTER COLUMBUS (DSCC-VQ), COLUMBUS, OH 43216-5000.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI-CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW20 thru RW24		26-483-71	/2	Memcor-Truohm, Inc.
Char. V, min. wire size 0.00175"				
RW20: 0.1 ohm thru 3,200 ohms	OR20			
RW21: 0.1 ohm thru 6,600 ohms	OR21			
RW22: 0.1 ohm thru 13,000 ohms	OR22			
RW23: 0.1 ohm thru 19,000 ohms	OR23			
RW24: 0.1 ohm thru 25,000 ohms	OR24			
RW20 thru RW24		26-823-66	/2	Ohmite Manufacturing Co. (1)
Char. V, min. wire size 0.00175"				
RW20: 0.1 ohm thru 8,200 ohms	RW20			
RW21: 0.1 ohm thru 16,000 ohms	RW21			
RW22: 0.1 ohm thru 36,000 ohms	RW22			
RW23: 0.1 ohm thru 51,000 ohms	RW23			
RW24: 0.1 ohm thru 75,000 ohms	RW24			
RW29 thru RW39, and RW47		26-792A-66	/3	Memcor-Truohm, Inc.
Char. V, min. wire size 0.00175"				
RW29: 0.1 ohm thru 1,500 ohms	FR-RW29			
RW30: 0.1 ohm thru 750 ohms	FR-RW30			
RW31: 0.1 ohm thru 1,800 ohms	FR-RW31			
RW32: 0.1 ohm thru 2,400 ohms	FR-RW32			
RW33: 0.1 ohm thru 4,700 ohms	FR-RW33			
RW34: 0.1 ohm thru 8,200 ohms	FR-RW34			
RW35: 0.1 ohm thru 11,000 ohms	FR-RW35			
RW36: 0.1 ohm thru 15,000 ohms	FR-RW36			
RW37: 0.1 ohm thru 24,000 ohms	FR-RW37			
RW38: 0.1 ohm thru 39,000 ohms	FR-RW38			
RW39: 0.1 ohm thru 51,000 ohms	FR-RW39			
RW47: 0.1 ohm thru 43,000 ohms	FR-RW47			
RW29, RW3l, RW33, RW35, RW37, RW38, RW47		26-45-77	/3	Ohmite Manufacturing Co. (1)
Char. N, min. wire size 0.00175"				
RW29: 0.1 ohm thru 2,700 ohms	RW29N			
RW31: 0.1 ohm thru 3,300 ohms	RW31N			
RW33: 0.1 ohm thru 8,100 ohms	RW33N			
RW35: 0.1 ohm thru 20,000 ohms	RW35N			
RW37: 0.1 ohm thru 43,000 ohms	RW37N			
RW38: 0.1 ohm thru 75,000 ohms	RW38N			
RW47: 0.1 ohm thru 81,000 ohms	RW47N			

DISTRIBUTION STATEMENT A . Approved for public release; distribution is unlimited.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI-CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW29 thru RW39, and RW47		26-824-66	/3	Ohmite Manufacturing Co. (1)
Char. V, min. wire size 0.00175"				
RW29: 0.1 ohm thru 2,700 ohms	RW29			
RW30: 0.1 ohm thru 2,700 ohms	RW30			
RW31: 0.1 ohm thru 6,800 ohms	RW31			
RW32: 0.1 ohm thru 10,000 ohms	RW32			
RW33: 0.1 ohm thru 18,000 ohms	RW33			
RW34: 0.1 ohm thru 30,000 ohms	RW34			
RW35: 0.1 ohm thru 43,000 ohms	RW35			
RW36: 0.1 ohm thru 56,000 ohms	RW36			
RW37: 0.1 ohm thru 91,000 ohms	RW37			
RW38: 0.1 ohm thru 0.15 megohm	RW38			
RW39: 0.1 ohm thru 0.20 megohm	RW39			
RW47: 0.1 ohm thru 0.18 megohm	RW47			
RW55 and RW56	HLR	26-793-66	/4	Memcor-Truohm, Inc.
Char. V. min. wire size 0.00175"				
RW55: 0.1 ohm thru 5,100 ohms				
RW56: 0.1 ohm thru 9,100 ohms				
RW55 and RW56	56AC	26-73-67	/4	Pacific Resistor Co.
Char. V, min. wire size 0.00175"				
RW55: 0.1 ohm thru 5,100 ohms				
RW56: 0.1 ohm thru 9,100 ohms				
RW55 and RW56		39007-440-70	/4	RCL Shallcross, Inc.
Char V, min. wire size 0.00175"		26-49-90		
RW55: 0.1 ohm thru 3,400 ohms	T-7A-55			
RW56: 0.1 ohm thru 9,100 ohms	T-10-A-56			
RW55	TS5C	39007-332-87	/4	Tepro of Florida, Inc.
Char. V, min. wire size 0.00175", 0.1 ohm thru 5,100 ohms				
RW67 thru RW69		26-719-66	/4	Dale Electronics, Inc. (1)
Char. V, min. wire size 0.001"				
RW67: 0.1 ohm thru 8,200 ohms	RS-5-70, RS-5-171			
RW68: 0.1 ohm thru 20,000 ohms	RS-10-39, RS-10-171			
RW69: 0.1 ohm thru 2,000 ohms	RS-2C-23, RS-2C-171			
RW67 thru RW69		26-86-81	/4	Dale Electronics, Inc. (2)
Char. V, min. wire size 0.001"				
RW67: 0.1 ohm thru 8,200 ohms	RS-5-70, RS-5-171			
RW68: 0.1 ohm thru 20,000 ohms	RS-10-39, RS-10-171			
RW69: 0.1 ohm thru 2,000 ohms	RS-2C-23, RS-2C-171			
RW67 thru RW69		26-1115-67	/4	Memcor-Truohm, Inc.
Char. V, min. wire size 0.00175"				
RW67: 0.1 ohm thru 3,600 ohms	RW67			
RW68: 0.1 ohm thru 8,200 ohms	RW68			
RW69: 0.1 ohm thru 910 ohms	RW69			
RW67 thru RW69		26-795-68	/4	Ohmite Manufacturing Co. (2)
Char. V, min. wire size 0.001"		26-349-87		
RW67: 0.1 ohm thru 8,200 ohms	85J			
RW68: 0.1 ohm thru 20,000 ohms	80J			
RW69: 0.1 ohm thru 2,000 ohms	83J			
RW67 thru RW69		26-350-87	/4	Ohmite Manufacturing Co. (2)
Char. V, min. wire size 0.001"				
RW67: 0.1 ohm thru 8,200 ohms	25J			
RW68: 0.1 ohm thru 20,000 ohms	20J			
RW69: 0.1 ohm thru 2,000 ohms	23J			
RW67 thru RW69		26-351-87	/4	Ohmite Manufacturing Co. (2)
Char. V, min. wire size 0.001"				
RW67: 0.1 ohm thru 8,200 ohms	95J			
RW68: 0.1 ohm thru 20,000 ohms	90J			
RW69: 0.1 ohm thru 2,000 ohms	93J			

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI-CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW67 thru RW69 Char. V, min. wire size 0.001" RW67: 0.l ohm thru 8,200 ohms RW68: 0.1 ohm thru 20,000 ohms RW69: 0.1 ohm thru 2,000 ohms	 5A 10A MN1A	26-563-67	/4	Pacific Resistor Co.
RW67 thru RW69 Char. V, min. wire size 0.001" RW67: 0.1 ohm thru 8,200 ohms RW68: 0.1 ohm thru 20,000 ohms RW69: 0.1 ohm thru 2,000 ohms	 LA419 LA433 LA417	26-603-69	/4	RCL Shallcross, Inc.
RW69 Char. V, min. wire size 0.0001", res. tol. 0.1 ohm thru 2,000 ohms.	TS2C	39007-332-87	/4	Tepro of Florida, Inc.
RW70 and RW79 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW70: 0.1 ohm thru 2,740 ohms RW79: 0.1 ohm thru 6,490 ohms	 RS-1A-300, RS-1A-125 RS-2B-300, RS-2B-125	26-208-66	/5	Dale Electronics, Inc. (1)
RW70 and RW79 Char. U, min. wire size 0.001", res. tol. F RW70: 0.1 ohm thru 1,210 ohms RW79: 0.1 ohm thru 2,430 ohms	 RS-1A-300, RS-1A-125 RS-2B-300, RS-2B-125	26-85-81	/5	Dale Electronics, Inc. (2)
RW70 and RW79 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW70: 0.1 ohm thru 3,160 ohms RW79: 0.1 ohm thru 10,500 ohms	 81B 83B	26-348-87	/5	Ohmite Manufacturing Co. (2)
RW70 and RW79 Char. U, min. wire size 0.0008", res. tol. F. RW70: 0.1 ohm thru 3,160 ohms RW79: 0.1 ohm thru 6,040 ohms	 15A N1A	26-75-67	/5	Pacific Resistor Co.
RW70 and RW79 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW70: 0.1 ohm thru 3,160 ohms RW79: 0.1 ohm thru 10,500 ohms	 LA449 LA461	26-972-71	/5	RCL Shallcross, Inc.
RW70 and RW79 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW70: 0.1 ohm thru 3,160 ohms RW79: 0.1 ohm thru 6,040 ohms	 TS1A TS2B	39007-333-87 39007-332-87	/5	Tepro of Florida, Inc.
RW74 and RW78 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW74: 0.1 ohm thru 24,300 ohms RW78: 0.1 ohm thru 71,500 ohms	 RS-5-69, RS-5-125 RS-10-38, RS-10-125	26-207-66	/5	Dale Electronics, Inc. (1)
RW74 and RW78 Char. U, min. wire size 0.001", res. tol. F. RW74: 0.1 ohm thru 9,090 ohms RW78: 0.1 ohm thru 26,700 ohms	 RS-5-69, RS-5-125 RS-10-38, RS-10-125	26-020-97	/5	Dale Electronics, Inc. (2)
RW74 and RW78 Char. U, min. wire size 0.0008", res. tol. F. RW74: 0.1 ohm thru 38,300 ohms RW78: 0.1 ohm thru 51,100 ohms	 SL-0005 SL-0010	26-73-85	/5	Memcor-Truohm, Inc.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI-CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW74 and RW78 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW74: 0.1 ohm thru 38,300 ohms RW78: 0.1 ohm thru 90,900 ohms	 85B 80B	26-347-87	/5	Ohmite Manufacturing Co. (2)
RW74 and RW78 Char. U, min. wire size 0.001", res. tol. F. RW74: 0.1 ohm thru 12,100 ohms RW78: 0.1 ohm thru 40,200 ohms	 5AV 10AV	26-74-67	/5	Pacific Resistor Co.
RW74 and RW78 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW74: 0.1 ohm thru 38,300 ohms RW78: 0.1 ohm thru 90,900 ohms	 LA446 LA433	26-971-71	/5	RCL Shallcross, Inc.
RW74 and RW78 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW74: 0.1 ohm thru 12,100 ohms RW78: 0.1 ohm thru 39,200 ohms	 TSA5 TS10	39007-332-87	/5	Tepro of Florida, Inc.
RW74 and RW78 Char. U, min. wire size 0.0008", res. tol. F. RW74: 0.1 ohm thru 38,300 ohms RW78: 0.1 ohm thru 51,100 ohms	 SL-0005 SL-0010	26-73-85	/5	Memcor-Truohm, Inc.
RW79 Char. U, min. wire size 0.0008", res. tol. F, 0.1 ohm thru 6,490 ohms.	RS-2B-300, RS-2B-125	26-1060-76	/5	Dale Electronics, Inc. (1)
RW79 Char. U, min. wire size 0.001", res. tol. F, 0.1 ohm thru 2,430 ohms.	RS-2B-300, RS-2B-125	26-022-97	/5	Dale Electronics, Inc. (2)
RW79 Char. U, min. wire size 0.0008", res. tol. F, 10 ohms thru 6,040 ohms.	SL-0003	26-73-85	/5	Memcor-Truohm, Inc.
RW79 Char. U, min. wire size 0.0008", res. tols. B, D, F, 0.1 ohm thru 10,500 ohms.	LM261 TM-2B-79	39007-1372-85	/5	RCL Shallcross, Inc.
RW80 and RW81 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW80: 0.1 ohm thru 2,740 ohms RW81: 0.1 ohm thru 1,000 ohms	 G-3-125, G-3-380 G-1-125, G-1-380	26-209-66	/6	Dale Electronics, Inc. (1)
RW80 and RW81 Char. U, min. wire size 0.0008", res. tol. F. RW80: 0.1 ohm thru 3,160 ohms RW81: 0.1 ohm thru 649 ohms	 B3 B1	26-76-67	/6	Pacific Resistor Co.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI-CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
RW80 and RW81 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW80: 0.1 ohm thru 3,160 ohms RW81: 0.1 ohm thru 1,000 ohms	 LA49, LM249 TM-1-80 LA68, LA268, LM268 TM-1/2-A81	26-475-72 39007-1076-87 39007-1371-70	/6	RCL Shallcross, Inc.
RW80 and RW81 Char. U, min. wire size 0.0008", res. tols. B, D, and F. RW80: 0.1 ohm thru 3,160 ohms RW81: 0.1 ohm thru 1,000 ohms	 TG3 TG1	39007-333-87	/6	Tepro of Florida, Inc.

MANUFACTURER'S NAME, ADDRESS AND PLANT	CAGE CODE
Dale Electronics, Inc. 1122 23rd Street P.O. Box 609 Columbus, NE 68601 Plants: 1. Same Address 2. Electronica Dale De Mexico S.A. DE C.V. A Vishay Co. Avenue Insurgentes No. 606 C.D. Juarez, Chihuahua Mexico	91637
Memcor-Truohm, Inc. 1320 Flaxmill Road Huntington, IN 46750 Plant: Same Address	24681
Ohmite Manufacturing Company 3601 Howard Street Skokie, IL 60076 Plant 1. Same Address 2. Railroad Avenue, R.R. #1 Princeton, IL 61356	44655
Pacific Resistor Company 18300 Oxnard Street Tarzana, CA 91356 Plant: Same Address	06416
RCL Shallcross, Inc. U.S. 70 East Smithfield, NC 27577 Plant: Same Address	54294
Tepro of Florida, Inc. 2608 Enterprise Road P.O. Box 1260 Clearwater, FL 33517 Plant: Same Address	15915