QUALIFICATIONS VALIDATED
EVERY TWO YEARS

QPL-12934-51
02-Aug-05
SUPERSEDING
QPL-12934-50
08-Aug-03

QUALIFIED PRODUCTS LIST
OF
PRODUCTS QUALIFIED UNDER PERFORMANCE SPECIFICATION
MIL-PRF-12934
RESISTOR, VARIABLE, WIRE WOUND, PRECISION,
GENERAL SPECIFICATION FOR

This list has been prepared for use by or for the Government in the acquisition of products covered by Specification MIL-PRF-12934. Listing of a product is not intended to and does not connote endorsement of the product by the Department of Defense. All products listed herein have been qualified under the requirements for the product as specified in the latest effective issue of the applicable specification. This list is subject to change without notice; revision or amendment of this list will be issued as necessary. The listing of a product does not release the supplier from compliance with the specification requirements.

The activity responsible for this QPL is the Defense Supply Center Columbus (DSCC-VQ), Columbus, OH 43218-3990.

* Procurement of Category II resistors shall be confined to sources of the corresponding Category I resistor. Also, only manufacturers having their resistors annotated with an asterisk (*) have complied with the quality assurance program requirements (Appendix B of MIL-R-12934H) and are eligible to supply similar Category II resistors within the limitations specified in paragraph 4.4.4 of MIL-R-12934H. (See paragraphs 3.2.1 and 3.2.2 of MIL-R-12934H for definitions of Category I and II resistors.)

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFICATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RR0900*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 10000 ohms	1211	12934-42-76	/1	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 10000 ohms	78WS	12934-505-77	/1	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 10000 ohms	701	12934-593-73	/1	Spectrol Electronics Corp.
RR1000*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50000 ohms	3211	12934-43-76	/6	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50000 ohms	1098-080	12934-16-7T	/6	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50000 ohms	501	12934-583-77A	/6	Spectrol Electronics Corp.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATIO N REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RR1004*				
Func. and shaft lengths D; classes 2, 4; res. temp. chars. A; rotational life chars. 9; function conformity tol. and res. tol. chars. B; nom. total res. value 100000 ohms	3210-2216	12934-43-76	/34 (TD)	BEI Duncan Electronics
Func. and shaft lengths D; classes 2, 4; res. temp. chars. A; rotational life chars. 9; function conformity tol. and res. tol. chars. B; nom. total res. value 100000 ohms	1098-081	12934-16-7T	/34 (TD)	Honeywell-New England Instrument Div.
RR1100*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, E, F, G, H, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 20000 ohms	1311	12934-42-76	/2	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. , G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 20000 ohms	116WS	12934-505-77	/2	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 20000 ohms	121	12934-593-73	/2	Spectrol Electronics Corp.
RR1300*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 40000 ohms	1511	12934-42-76	/19	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 40000 ohms	176WS	12934-506-77	/19	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 40000 ohms	171	12934-593-73	/19	Spectrol Electronics Corp.
RR1400*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 200000 ohms	3511	12934-43-76	/20	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 200000 ohms	1070-080	12934-16-7T	/20	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 200000 ohms	871	12934-594-73	/20	Spectrol Electronics Corp.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATIO N REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RR2000*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 60000 ohms	1711	12934-42-76	/4	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 60000 ohms	200WS	12934-506-77	/4	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, E, F, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 60000 ohms	301	12934-593-73	/4	Spectrol Electronics Corp.
RR2002*				
Func. and shaft lengths H; classes 2, 4; res. temp. chars. A; rotational life chars. 9; function conformity tol. and res. tol. chars. U; nom. total res. value 20000 ohms	3710-986	12934-43-76	/33 (TD)	BEI Duncan Electronics
RR2100*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 250000 ohms	3711	12934-43-76	/9	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 250000 ohms	1088-080	12934-16-7T	/9	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 250000 ohms	801	12934-594-73	/9	Spectrol Electronics Corp.
RR2104*				
Func. and shaft lengths F; classes 2, 4; res. temp. chars. A; rotational life chars. 8; function conformity tol. and res. tol. chars. L; nom. total res. value 20000 ohms	3710-987	12934-43-76	/35 (TD)	BEI Duncan Electronics
Func. and shaft lengths F; classes 2, 4; res. temp. chars. A; rotational life chars. 8; function conformity tol. and res. tol. chars. L; nom. total res. value 20000 ohms	1088-081	12934-16-7T	/35 (TD)	Honeywell-New England Instrument Div.
RR3000*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 100000 ohms	1811	12934-42-76	/5	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 100000 ohms	300WS	12934-506-77	/5	Honeywell-New England Instrument Div.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATIO N REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 100000 ohms	401	12934-593-73	/5	Spectrol Electronics Corp.
RR3100*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, G, H, M, N, O, S, T, U; nom. total res. values 100 ohms thru 10000 ohms	1212	12934-42-76	/10	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 10000 ohms	78WB	12934-505-77	/10	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, S, T, U; nom. total res. values 100 ohms thru 10000 ohms	701	12934-593-73	/10	Spectrol Electronics Corp.
RR3200*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 20000 ohms	1312	12934-42-76	/15	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 20000 ohms	116WB	12934-505-77	/15	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 20000 ohms	121	12934-593-73	/15	Spectrol Electronics Corp.
RR3300*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 40000 ohms	1512	12934-42-76	/16	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 40000 ohms	176WB	12934-506-77	/16	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 40000 ohms	171	12934-593-73	/16	Spectrol Electronics Corp.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATIO N REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RR3400*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 60000 ohms	1712	12934-42-76	/17	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 60000 ohms	200WB	12934-506-77	/17	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 60000 ohms	301	12934-593-73	/17	Spectrol Electronics Corp.
RR3500*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 200 ohms thru 100000 ohms	1812	12934-42-76	/18	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 200 ohms thru 100000 ohms	300WB	12934-506-77	/18	Honeywell-New England Instrument Div.
Func. and shaft lengths A, B, C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 200 ohms thru 100000 ohms	401	12934-593-73	/18	Spectrol Electronics Corp.
RR3600*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50000 ohms	3214	12934-43-76	/27	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50000 ohms	1094-080	12934-16-7T	/27	Honeywell-New England Instrument Div.
RR3601*				
Func. and shaft lengths D; classes 2, 4; res. temp. chars. A; rotational life chars. 9; function conformity tol. and res. tol. chars. K; nom. total res. value 10000 ohms	3210-2217	12934-43-76	/36 (TD)	BEI Duncan Electronics
Func. and shaft lengths D; classes 2, 4; res. temp. chars. A; rotational life chars. 9; function conformity tol. and res. tol. chars. K; nom. total res. value 10000 ohms	1094-081	12934-16-7	/36 (TD)	Honeywell-New England Instrument Div.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFICATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RR3700*				
Func. and shaft lengths C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50000 ohms	3215	12934-43-76	/28	BEI Duncan Electronics
Func. and shaft lengths C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50000 ohms	1093-080	12934-16-7T	/28	Honeywell-New England Instrument Div.
RR3800*				
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 100000 ohms	3217	12934-43-76	/29	BEI Duncan Electronics
Func. and shaft lengths A, B, C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 100000 ohms	1096-080	12934-16-7T	/29	Honeywell-New England Instrument Div.
RR3900*				
Func. and shaft lengths C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 100000 ohms	3218	12934-43-76	/30	BEI Duncan Electronics
Func. and shaft lengths C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 10000 ohms	1095-086	12934-16-7T	/30	Honeywell-New England Instrument Div.
RR4000*				
Func. and shaft lengths C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50000 ohms	3212	12934-43-76	/31	BEI Duncan Electronics
Func. and shaft lengths C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50000 ohms	1097-080	12934-16-7T	/31	Honeywell-New England Instrument Div.
Func. and shaft lengths C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50000 ohms	501	12934-583-77A	/31	Spectrol Electronics Corp.
RR4100*				
Func. and shaft lengths C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 250000 ohms	3712	12934-43-76	/32	BEI Duncan Electronics

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATIO N REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
Func. and shaft lengths C, D, E, F; classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 250000 ohms	1074-080	12934-16-7T	/32	Honeywell-New England Instrument Div.
Func. and shaft lengths C, D, E, F; classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 250000 ohms	801	12934-594-73	/32	Spectrol Electronics Corp.

Manufacturer and Supplier Location Information

Manufacturer: BEI Duncan Electronics (CAGE Code: 11534)
Location: 170 Technology Drive, Irvine, CA 92618-2401, US

Plant Location: Same Address as Manufacturer

Manufacturer: Honeywell-New England Instrument Div. (CAGE Code: 08815)
Location: 245 Railroad Street, Woonsocket, RI 02895, US

Plant Location: Same Address as Manufacturer

Manufacturer: Spectrol Electronics Corp. (CAGE Code: 02111)
Location: 4051 Greystone Drive, Ontario, CA 91761-3100, US

Plant Location: Same Address as Manufacturer