QUALIFIED PRODUCTS LIST
OF
PRODUCTS QUALIFIED UNDER PERFORMANCE SPECIFICATION
MIL-PRF-12934
RESISTOR, VARIABLE, WIRE WOUND, PRECISION,
GENERAL SPECIFICATION FOR

This list has been prepared for use by or for the Government in the acquisition of products covered by Specification MIL-PRF-12934. Listing of a product is not intended to and does not connote endorsement of the product by the Department of Defense. All products listed herein have been qualified under the requirements for the product as specified in the latest effective issue of the applicable specification. This list is subject to change without notice; revision or amendment of this list will be issued as necessary. The listing of a product does not release the supplier from compliance with the specification requirements.

The activity responsible for this QPL is DLA Land and Maritime-VQ, Columbus, OH 43218-3990.

* Procurement of Category II resistors shall be confined to sources of the corresponding Category I resistor. Also, only manufacturers having their resistors annotated with an asterisk (*) have complied with the quality assurance program requirements (Appendix B of MIL-R-12934H) and are eligible to supply similar Category II resistors within the limitations specified in paragraph 4.4.4 of MIL-R-12934H. (See paragraphs 3.2.1 and 3.2.2 of MIL-R-12934H for definitions of Category I and II resistors.)

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RR0900*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 10 kilohms	1211	12934-42-76	/1	BEI Sensors
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 10 kilohms	701	12934-593-73	/1	Spectrol Electronics Corp.
RR1000*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50 kilohms	3211	12934-43-76	/6	BEI Sensors
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50 kilohms	501	12934-583-77A	/6	Spectrol Electronics Corp.
RR1004*				
Func. and shaft lengths D: classes 2, 4; res. temp. chars. A; rotational life chars. 9; function conformity tol. and res. tol. chars. B; nom. total res. value 100 kilohms	3210-2216	12934-43-76	/34 (TD)	BEI Sensors
RR1100*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, E, F, G, H, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 20 kilohms	1311	12934-42-76	/2	BEI Sensors

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 20 kilohms	121	12934-593-73	/2	Spectrol Electronics Corp.
RR1300*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 40 kilohms	1511	12934-42-76	/19	BEI Sensors
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 40 kilohms	171	12934-593-73	/19	Spectrol Electronics Corp.
RR1400*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 200 kilohms	3511	12934-43-76	/20	BEI Sensors
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 200 kilohms	871	12934-594-73	/20	Spectrol Electronics Corp.
RR2000*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 60 kilohms	1711	12934-42-76	/4	BEI Sensors
Func. and shaft lengths A, B, C, E, F, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 60 kilohms	301	12934-593-73	/4	Spectrol Electronics Corp.
RR2002*				
Func. and shaft lengths H: classes 2, 4; res. temp. chars. A; rotational life chars. 9; function conformity tol. and res. tol. chars. U; nom. total res. value 20 kilohms	3710-986	12934-43-76	/33 (TD)	BEI Sensors
RR2100*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 250 kilohms	3711	12934-43-76	/9	BEI Sensors
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 250 kilohms	801	12934-594-73	/9	Spectrol Electronics Corp.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RR2104*				
Func. and shaft lengths F: classes 2, 4; res. temp. chars. A; rotational life chars. 8; function conformity tol. and res. tol. chars. L; nom. total res. value 20 kilohms	3710-987	12934-43-76	/35 (TD)	BEI Sensors
RR3000*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 100 kilohms	1811	12934-42-76	/5	BEI Sensors
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 100 kilohms	401	12934-593-73	/5	Spectrol Electronics Corp.
RR3100*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, G, H, M, N, O, S, T, U; nom. total res. values 100 ohms thru 10 kilohms	1212	12934-42-76	/10	BEI Sensors
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, S, T, U; nom. total res. values 100 ohms thru 10 kilohms	701	12934-593-73	/10	Spectrol Electronics Corp.
RR3200*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 20 kilohms	1312	12934-42-76	/15	BEI Sensors
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 20 kilohms	121	12934-593-73	/15	Spectrol Electronics Corp.
RR3300*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 40 kilohms	1512	12934-42-76	/16	BEI Sensors
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 40 kilohms	171	12934-593-73	/16	Spectrol Electronics Corp.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
RR3400*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 60 kilohms	1712	12934-42-76	/17	BEI Sensors
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 100 ohms thru 60 kilohms	301	12934-593-73	/17	Spectrol Electronics Corp.
RR3500*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X; nom. total res. values 200 ohms thru 100 kilohms	401	12934-593-73	/18	Spectrol Electronics Corp.
RR3601*				
Func. and shaft lengths D: classes 2, 4; res. temp. chars. A; rotational life chars. 9; function conformity tol. and res. tol. chars. K; nom. total res. value 10 kilohms	3210-2217	12934-43-76	/36 (TD)	BEI Sensors
RR3800*				
Func. and shaft lengths A, B, C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 100 kilohms	3217	12934-43-76	/29	BEI Sensors
RR3900*				
Func. and shaft lengths C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 100 kilohms	3218	12934-43-76	/30	BEI Sensors
RR4000*				
Func. and shaft lengths C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50 kilohms	3212	12934-43-76	/31	BEI Sensors
Func. and shaft lengths C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 100 ohms thru 50 kilohms	501	12934-583-77A	/31	Spectrol Electronics Corp.
RR4100*				
Func. and shaft lengths C, D, E, F: classes 2, 4; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 250 kilohms	3712	12934-43-76	/32	BEI Sensors

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
Func. and shaft lengths C, D, E, F: classes 2, 3, 4, 5; res. temp. chars. A, B, C, D, E, F, G, H; rotational life chars. 7, 8, 9; function conformity tol. and res. tol. chars. G, H, I, J, K, L, S, T, U, V, W, X; nom. total res. values 200 ohms thru 250 kilohms	801	12934-594-73	/32	Spectrol Electronics Corp.

Manufacturer and Supplier Location Information

Manufacturer: BEI Sensors (CAGE Code: 11534)
Location: 7230 Hollister Avenue, Goleta, CA 93117, US

Plants:
1. Plant: Same Address as Manufacturer

Manufacturer: Spectrol Electronics Corp. (CAGE Code: 02111)
Location: 4051 Greystone Drive, Ontario, CA 91761-3100, US

Plants:
1. Plant: Same Address as Manufacturer