Specification Details: **Date: 11/8/2021**

Specification: MIL-DTL-15109
Title: Resistors and Rheostats, Naval Shipboard
Federal Supply Class (FSC): 5905
Conventional: Yes
Specification contains quality assurance program: No
MIL-STD-790 Established Reliability & High Reliability: No
MIL-STD-690 Failure Rate Sampling Plans & Procedures: No
Weibull Graded: No
Specification contains space level reliability requirements: No
Specification allows test optimization: No

Contact Information:

Office of Primary Involvement: Passive Devices Branch, DLA Land and Maritime - VQP
Primary Qualifying Activity Contact: 614-692-3757, e-mail: vqp.dl@dla.mil
Secondary Qualifying Activity Contact: 614-692-0609, e-mail: vqp.do@dla.mil

Notes:

N/A

Part Configuration:

PART LISTINGS

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
Form: EW (Exposed Wire) Type: Fixed, with or without taps or adjustable Rating: 120 to 550 watts; .03 to 133 ohms	Corrib Resistor	Ohmite Rpt. 3882X-2	Ohmite Manufacturing Co.
Form: EW (Exposed Wire) Type: Fixed, with taps Rating: .32 to .7 ohms; 11 to 68 amps	A11229 Resistor Assembly for XAG-8A Commutator Assembly	Ohmite Rpt. 5301X-SR	Ohmite Manufacturing Co.
Form: EW (Exposed Wire) Type: Unenclosed and enclosed standard and locking bushing Rating: 12.5 watts; 1 to 15000 ohms	Model E, Rheostat	Ohmite Rpt. 5343X-SR	Ohmite Manufacturing Co.
Form: EW (Exposed Wire) Type: Unenclosed and enclosed standard and locking bushing Rating: 75 watts; .5 to 10000 ohms	Model G, Rheostat	Ohmite Rpt. 5343X-SR	Ohmite Manufacturing Co.
Form: EW (Exposed Wire) Type: Unenclosed and enclosed standard and locking bushing Rating: 25 watts; 1 to 25000 ohms	Model H, Rheostat	Ohmite Rpt. 5343X-SR	Ohmite Manufacturing Co.
Form: EW (Exposed Wire) Type: Unenclosed and enclosed standard Rating: 50 watts; .5 to 50000 ohms	Model J, Rheostat	Ohmite Rpt. 5343X-SR	Ohmite Manufacturing Co.
Form: EW (Exposed Wire) Type: Unenclosed and enclosed standard and locking bushing Rating: 100 watts; .5 to 10000 ohms	Model K, Rheostat	Ohmite Rpt. 5343X-SR	Ohmite Manufacturing Co.
Form: IW (Embedded Wire) Type: Fixed, with or without taps or adjustable Rating: 5 to 160 watts; .27 to 125000 ohms	Vitreous Enameled Resistor	Ohmite Rpt. 3882X-1	Ohmite Manufacturing Co.

Manufacturer and Supplier Location Information

Manufacturer: Ohmite Manufacturing Company (CAGE Code: 44655)

Location: 27501 Bella Vista Parkway, Warrenville, IL 60555, US

Plants:

1. Victoreen de Mexico, S.A. de C.V., Oriente 2, #46, Esq. Lorenzo de la Garza, Cd. Industrial H. Matamoros, Tamaulipas 87494, MX