Specification Details: **Date: 5/8/2012**

Specification: MIL-PRF-39001
Title: Capacitor, Fixed, Mica Dielectric
Federal Supply Class (FSC): 5910
Conventional: No
Specification contains quality assurance program: No
MIL-STD-790 Established Reliability & High Reliability: Yes
MIL-STD-690 Failure Rate Sampling Plans & Procedures: Yes
Weibull Graded: No
Specification contains space level reliability requirements: No
Specification allows test optimization: Yes

Contact Information:

Office of Primary Involvement: Passive Devices Branch, DLA Land and Maritime - VQP
Primary Qualifying Activity Contact: 614-692-0597, e-mail: vqp.jz@dla.mil
Secondary Qualifying Activity Contact: 614-692-0609, e-mail: vqp.do@dla.mil

Notes:

THE ACTIVITY RESPONSIBLE FOR THIS QPL IS THE U.S. ARMY COMMUNICATIONS-ELECTRONICS COMMAND AND FORT MONMOUTH. The activity designated as agent for all contacts relative to this QPL is DLA Land and Maritime VQ, Columbus, OH 43218-3990.

Part Configuration:

CMR04C1R0DODM

Style	Characteristic	Capacitance	Capacitance Tolerance	Operating Temperature Range	Rated Voltage	Product Level Designator
CMR04	C	1R0	D	O	D	M

PART LISTINGS

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
CMR03				
Chars. C, E, F; voltage 50, 100, 300; cap. values 1 pF thru 400 pF; tols. D, G, J; oper. temp. range O; product level M, P, R		39001-112-96; 39001-113-96	/5	Cornell-Dubilier
CMR04				
Chars. C, E, F; voltage 100, 300, 500; cap. values 1 pF thru 390 pF; tols. D, F, G, J; oper. temp. range O, P; product level M, P, R		39001-112-96; 39001-113-96	/5	Cornell-Dubilier
CMR05				
Chars. C, E, F; voltage 500; cap. values 1 pF thru 390 pF; tols. D, F, G, J; oper. temp. range O, P; product level M, P, R		39001-112-96; 39001-113-96	/5	Cornell-Dubilier
CMR06				
Chars. F; voltage 500; cap. values 430 pF thru 4700 pF; tols. F, G, J; oper. temp. range O, P; product level M, P, R		39001-112-96; 39001-113-96	/5	Cornell-Dubilier
CMR07				
Chars. F; voltage 500; cap. values 5100 pF thru 20000 pF; tols. F, G, J; oper. temp. range O, P; product level M, P, R		39001-112-96; 39001-113-96	/5	Cornell-Dubilier
CMR08				
Chars. F; voltage 100, 300, 500; cap. values 22000 pF thru 91000 pF; tols. F, G, J; oper. temp. range O, P; product level M, P, R		39001-112-96; 39001-113-96	/5	Cornell-Dubilier

Manufacturer and Supplier Location Information

Manufacturer: Cornell-Dubilier (CAGE Code: 00853)
Location: 140 Technology Place, Liberty, SC 29657, US

Plants:

1. C.D. Electronics De Mexico S.A. DE C.V., CAGE: 00853, Boulevard Benito, Juarez KM 5.5, Mexicali, B.C., Mexico