QUALIFICATIONS VALIDATED
SEMIANNUALLY

QPL-49470-3
2 May 2000
SUPERSEDING
QPL-49470-2
9 November 1999

QUALIFIED PRODUCTS LIST

OF

PRODUCTS QUALIFIED UNDER PERFORMANCE SPECIFICATION

MIL-PRF-49470

CAPACITOR, FIXED, CERAMIC DIELECTRIC, SWITCH MODE POWER SUPPLY

(GENERAL PURPOSE AND TEMPERATURE STABLE), STANDARD RELIABILITY AND HIGH RELIABILITY

GENERAL SPECIFICATION FOR

This list has been prepared for use by or for the Government in the acquisition of products covered by subject specification and such listing of a product is not intended to and does not connote endorsement of the product by the Department of Defense. All products listed herein have been qualified under the requirements for the product as specified in the latest effective issue of the applicable specification. This list is subject to change without notice; revision or amendment of this list will be issued as necessary. The listing of a product does not release the supplier from compliance with the specification requirements.

THE ACTIVITY RESPONSIBLE FOR THIS QPL IS THE U.S. ARMY COMMUNICATIONS-ELECTRONICS COMMAND AND FORT MONMOUTH. The activity designated as agent for all contacts relative to this QPL is the Defense Supply Center Columbus (DSCC-VQ), Columbus, OH 43216-5000.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI-CATION	MANUFACTURER'S NAME AND ADDRESS
PS01 All cap. values and tols., in 50 and 100 volts, BX char.	SM06	49470-133-98 49470-132-98	/1	Olean Advanced Products Division of AVX Corp. 1696 Seneca Avenue Olean, NY 14760
PS02 All cap. values and tols., in 50 and 100 volts, BX char.	SM96	49470-133-98 49470-132-98	/2	Plant: Same Address Cage Code: 96095
PS01 Cap. values 0.68 thru 8.2µF, case codes 4 and 5, tols. K and M, in 100 volts, BX char.	HRS506	49470-031-98	/1	Presidio Components, Inc. 7169 Construction Court Plant: Same Address Cage Code: 60212
Cap. values 1 thru 15µF, case codes 4 and 5, tols. K and M, in 50 volts, BX char.	HRS506	49470-031-98	/1	
Cap. values 0.15 thru 5.6µF, case codes 3, 4, and 5, tols. K and M, in 500 volts, BQ char.	HRS513	49470-031-98	/1	

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.